

## PRODUCT FACT SHEET

## SLEDGE® HEADLAMP RUGGEDIZED RECHARGEABLE HEADLAMP

**DESCRIPTION:** The Sledge® is a ruggedized, rechargeable, flood headlamp designed for versatility and performance for industrial

applications and outdoor use. It features dual power LEDs and offers four total output modes. Powered by the SL-B26® protected Li-Ion USB rechargeable battery pack, it can also operate on two CR123A lithium batteries. Packaged with a USB-C charging cable, elastic head and rubber head hard hat straps, and one SL-B26® battery.

**CASE MATERIAL:** Tough Polycarbonate thermoplastic construction with aluminum faceplate. Available in Black.

**DIMENSIONS:** Height: 1.57 in. (4.0 cm) Width: 3.74 in. (9.5 cm) Front to Back: 1.73 in (4.4 cm)

WEIGHT: 4.6 oz (121.9 grams) with SL-B26® battery pack

LENS: Unbreakable polycarbonate lens.

LIGHT SOURCE: Two (2) White LEDs, impervious to shock with a 50,000 hour lifetime.

**LIGHT OUTPUT:** See chart. Regulated output for consistent lumen performance over the battery life.

ON/OFF: Multi-function push button switch. High, Medium, Low and Off

THRO® Mode: Press and hold the button for 3 seconds while light is on, after 60 seconds, light reverts to prior

mode

NOTE: If more than two seconds pass between button presses, the next press will turn the light off

**RUN TIME:** See charts. All claims to 10% of initial lumen output.

**BATTERY:** One (1) Streamlight® SL-B26® protected Li-Ion USB rechargeable battery pack with on-board safety

control, 2600mAh, rechargeable up to 500 times. Recharges in 5 hours.

**FEATURES:** Aluminum faceplate.

45° tilting head.

IPX4 rated for water resistant operation. 2 meter impact resistance tested.

Serialized for positive identification. Rubber hard hat and elastic head straps.

WARRANTY: Streamlight's Limited Lifetime Warranty

**APPROVALS:** C∈ ≤ Meets applicable United Kingdom and European Community Directives

**OPTIONAL** 

**ACCESSORIES:** Hard hat clips, rubber hard hat and elastic head straps

**OUTPUT** 

RUNTIME

DISTANCE

INTENSITY

FL1 STANDARD	THRO	HIGH	MED	LOW
314	1000 LUMENS	600 LUMENS	300 LUMENS	100 LUMENS
0	60s	4h15min	9h15min	13h
	110m	85 m	58m	35 m
	3000 cd	1800cd	850cd	310cd

Performance Tested with SL-B26® Battery

Issued: 07/21/2025