

PRODUCT FACT SHEET

SLEDGE® HEADLAMP RUGGED RECHARGEABLE HEADLAMP

DESCRIPTION: The Sledge® is a rugged, rechargeable, flood headlamp designed for versatility and performance for industrial

applications and outdoor use. It features dual power LEDs and offers four total output modes. Powered by the SL-B26® protected Li-Ion USB rechargeable battery pack, it can also operate on two CR123A lithium batteries. Packaged with a USB-C charging cable, elastic head and rubber head hardhat straps, and one SL-B26® battery.

CASE MATERIAL: Tough Polycarbonate thermoplastic construction with aluminum faceplate. Available in Black.

DIMENSIONS: Height: 1.57 in. (4.0 cm) Width: 3.74 in. (9.5 cm) Front to Back: 1.73 in (4.4 cm)

WEIGHT: 4.6 oz (121.9 g) with SL-B26® battery pack

LENS: Unbreakable polycarbonate lens.

LIGHT SOURCE: Two (2) White LEDs, impervious to shock with a 50,000 hour lifetime.

LIGHT OUTPUT: See chart. Regulated output for consistent lumen performance over the battery life.

ON/OFF: Multi-function push button switch. High, Medium, Low and Off.

THRO® Mode: Press and hold the button for 3 seconds while light is on, after 60 seconds, light reverts to prior

mode.

NOTE: If more than two seconds pass between button presses, the next press will turn the light off.

RUN TIME: See charts. All claims to 10% of initial lumen output.

BATTERY: One (1) Streamlight SL-B26® protected Li-Ion USB rechargeable battery pack with on-board safety

control, 2600mAh, rechargeable up to 500 times. Recharges in 5 hours.

FEATURES: Aluminum faceplate.

45° tilting head.

IPX4 rated for water resistant operation.

2 meter impact resistance tested.

Low battery indicator - Headlamp blinks twice at regular intervals for the last 15 minutes of "usable" light.

Serialized for positive identification. Rubber hard hat and elastic head straps

WARRANTY: Streamlight's Limited Lifetime Warranty

OPTIONAL

ACCESSORIES: Hard hat clips, rubber hard hat and elastic head straps

OUTPUT

RUNTIME

DISTANCE

INTENSITY

FL1 STANDARD	THRO	HIGH	MED	LOW
31/5	1000 LUMENS	600 LUMENS	300 LUMENS	100 LUMENS
0	60s	4h15min	9h15min	13h
	110m	85 m	58m	35 m
	3000 cd	1800cd	850cd	310cd

Performance Tested with SL-B26® Battery

Issued: 07/21/2025 Revised: 09/23/2025

Revised: 09/23/2025 Rev: 2 Made in China Document #442