



## PROTAC® RAIL MOUNT VIR PRO MULTI-FUEL, WHITE & IR LONG GUN LIGHT

<b>DESCRIPTION:</b>	Gun-mounted tactical light featuring visible white light along with IR illumination that can easily be changed via the head mounted switch. Features a cutoff that prevents unintentional visible illumination when operating in IR mode. Its Jack-Cap® tail cap switch offers operational switch redundancy – push-button operation or remote pressure switch operation. The rail clamp is designed to securely attach to rifles, carbines, and submachine guns with a MIL-STD-1913 rail or with the included M-LOK® mount, allowing for alternative mounting options to M-LOK® and M-LOK® compatible rail systems. The light is powered by (2) CR123A lithium batteries or (1) Streamlight USB rechargeable SL-B26® battery pack.		
<b>CASE MATERIAL:</b>	6000 Series machined aircraft aluminum with black anodized finish		
<b>DIMENSIONS:</b>	Length: 5.65 in (14.4 cm)	Head Width: 1.92 in (4.9 cm)	Height: 1.40 in (3.6 cm)
<b>WEIGHT:</b>	8.2 oz (231 g) with (2) CR123A batteries. 8.8 oz (249 g) with (1) SL-B26® rechargeable battery pack.		
<b>LENS:</b>	High-temperature, shock-mounted, anti-reflective coated, impact-resistant BOROFLOAT® glass.		
<b>LIGHT SOURCE:</b>	White LED; 940nm IR LED		
<b>LIGHT OUTPUT:</b>	High: 1,100 lumens; 40,000 candela peak beam intensity; 400m beam distance Medium: 540 lumens, 19,000 candela peak beam intensity; 276m beam distance Low: 120 lumens; 4,200 candela peak beam intensity; 130m beam distance IR: 2,300 mW (high), 600 mW (low)		
<b>ON/OFF:</b>	Multi-functional, push-button tail switch with momentary and constant on functions. Remote switch available in momentary only (included) and momentary/constant on versions (optional). TEN-TAP® programmable switch allows the user to select one of three different programs: <ul style="list-style-type: none"><li>• White light high only/IR high only (default)</li><li>• White light medium only/IR high-low</li><li>• White light low-high/IR low-high</li></ul>		
<b>RUN TIME:</b>	<b>CR123A:</b> High: 1.5 hours Medium: 2.75 hours Low: 11 hours IR: 1.25 hours (high) 7.25 hours (low)	<b>SL-B26:</b> High: 2 hours Medium: 3.75 hours Low: 14 hours IR: 2 hours (high) 9 hours (low)	
<b>BATTERY:</b>	(2) 3-volt CR123A lithium batteries with a storage life of 10 years or (1) Streamlight SL-B26® lithium-ion USB rechargeable battery pack with 5-hour recharge time		
<b>FEATURES:</b>	1,100 lumens and 2,300 mW IR provides illumination for various conditions Jack-Cap® tail cap offers push-button switch and port for a remote pressure switch Mounts directly to guns with MIL-STD-1913 (Picatinny) rails or M-LOK® and M-LOK® compatible rails Rotating head allows for precise placement next to the rail 2-meter impact resistance construction, extensively live fire tested IPX7-rated with standard push-button switch installed; waterproof to 1 meter for 30 minutes IPX4-rated with the remote pressure switch installed for water-resistant operation		
<b>APPROVALS:</b>	  Meets applicable United Kingdom and European Community Directives  CEC Compliant (USB models only)		
<b>WARRANTY:</b>	Streamlight's Limited Lifetime Warranty		

**OPTIONAL****ACCESSORIES:** Battery charge cradles, replacement batteries, remote pressure switches

All rights reserved. M-LOK® is a registered trademark of Magpul Industries Corp.

BOROFLOAT® is a registered trademark of SCHOTT AG.

Issued: 01/14/2026

Revised: Rev: 0

Engineered in the USA, Made in China.

Document #443