



PROTAC® RAIL MOUNT 1L-X PRO USB / PROTAC® RAIL MOUNT 1L-X PRO

DESCRIPTION:	The ProTac® Rail Mount 1L-X Pro is a compact, multi-fuel, high-output tactical light designed for short-barreled rifles, carbines, and submachine guns. Featuring the innovative Jack-Cap® tail cap, this light offers dual operational redundancy—choose push-button activation or remote pressure switch control for ultimate flexibility. The integrated port ensures secure attachment of the remote pressure switch, while the rail clamp system fits MIL-STD-1913 Picatinny rails. It also includes an M-LOK® mount for alternative mounting options on M-LOK® compatible rail systems. Powered by one (1) Streamlight SL-B9® rechargeable lithium-ion battery pack or one (1) CR123A battery, this tactical light delivers high lumen output for superior visibility in low-light environments. It is perfect for law enforcement, military, and tactical applications.		
CASE MATERIAL:	6000 Series machined aircraft aluminum with black anodized finish.		
DIMENSIONS:	Length: 4.64 in (11.79 cm)	Width: 1.37 in (3.48 cm)	Height: 1.72 in (4.37 cm)
WEIGHT:	5.5 oz (155.9g) with CR123A battery.		
	5.6 oz (158.8g) with SL-B9® rechargeable battery pack.		
LENS:	High-temperature, shock-mounted, AR coated, impact-resistant BOROFLOAT® glass.		
LIGHT SOURCE:	White LED impervious to shock with a 50,000-hour lifetime.		
LIGHT OUTPUT:	See chart. Solid state current regulation for consistent illumination level and the reflector produces a concentrated beam with optimum peripheral illumination.		
ON/OFF:	Multi-function, push-button tail switch with momentary and latching constant on operations. Momentary only remote switch included. TEN-TAP® programming allows the user to select one of three different programs: high/strobe (factory default), high only, or low/high.		
RUN TIME:	See chart.		
BATTERY:	One (1) 3-volt CR123A lithium battery with a storage life of 10 years. Also accepts one (1) Streamlight SL-B9® lithium-ion rechargeable battery pack.		
FEATURES:	Jack-Cap® tail cap offers push-button switch and port for a remote pressure switch. One-handed snap-on and tighten interface keeps hands away from muzzle when attaching/detaching from the firearm. Mounts directly to guns with MIL-STD-1913 (Picatinny) rails or M-LOK® and M-LOK® compatible rail systems. Extensively live fire tested, impact-resistant construction. IP67 rated with standard push-button switch installed; waterproof to 1 meter for 30 minutes. IP54 rated with the remote pressure switch installed for water-resistant operation.		
APPROVALS:	UK Meets applicable United Kingdom and European Community Directives CEC Compliant (USB model only)		
WARRANTY:	Streamlight's Limited Lifetime Warranty		
OPTIONAL ACCESSORIES:	Battery charge cradles, replacement batteries, remote pressure switches		

	SL-B9®		CR123A	
	High	Low	High	Low
OUTPUT (Lumens)	850	100	500	100
RUN TIME (Hours)	0.5	4.5	1.75	6.5
DISTANCE (Meters)	346	117	268	117
INTENSITY (Candela)	30,000	3,400	18,000	3,400
STROBE RUN TIME (Hours)	1.25		2.5	

All rights reserved. M-LOK® is a registered trademark of Magpul Industries Corp. BOROFLOAT® is a registered trademark of SCHOTT AG.