



TLR-3®X/TLR-3®X USB

CUSTOMIZABLE, RAIL-MOUNTED TACTICAL WEAPON LIGHT DESIGNED FOR USE WITH SUBCOMPACT AND COMPACT HANDGUNS

DESCRIPTION:

The TLR-3®X delivers powerful performance with multi-fuel battery capability, operating on either one (1) CR123A battery or one (1) Streamlight SL-B9® rechargeable lithium-ion battery pack. This compact weapon light delivers 500 lumens and 6,500 candela, providing exceptional brightness and beam distance for tactical applications. Featuring a narrow profile, reversible rail clamps, and multiple paddle switches, the TLR-3®X is designed for customizable fitment on a broad range of firearms. Its innovative design ensures quick and safe installation and removal without placing hands in front of the muzzle, enhancing user safety and convenience. Please refer to the below fitment guide for the current compatibility list.

CASE MATERIAL:

Impact and chemical-resistant, heat-stabilized, engineered polymer.

DIMENSIONS:

Width: 1.07 in (2.72 cm) Height: 1.29 in (3.28 cm) Length: 2.75 in (6.99 cm)

WEIGHT:

CR123A: 2.15 oz (60.9g) with battery.
SL-B9®: 2.25 oz (63.8g) with battery.

LENS:

High temperature, shock-mounted, impact & scratch-resistant BOROFLOAT® glass.

LIGHT SOURCE:

White LED, impervious to shock with a 50,000-hour lifetime.

LIGHT OUTPUT:

500 lumens, 6,500 candela peak beam intensity, and 161m beam distance.
Custom reflector produces a concentrated beam with optimum peripheral illumination.
Optimized electronics provide regulated intensity.

ON/OFF:

Rear switches left and right of the trigger guard provide ambidextrous operation.
Momentary and constant on operation. User-activated strobe.

RUN TIME:

CR123A: 1.5 hours of continuous operation to the 10% output level.
SL-B9®: 1 hour of continuous operation to the 10% output level.

BATTERY:

CR123A: One (1) 3-volt CR123A lithium battery with a storage life of 10 years.
SL-B9®: One (1) Streamlight Li-Ion 850mAh USB-C rechargeable battery pack with integrated safety circuit, rechargeable up to 500 cycles. Charges within 2.5 hours via optional USB-C cord or bank charger.
Battery installed/removed through face cap. No need to remove light from firearm.

FEATURES:

Reversible clamp system fits short and standard railed handguns (1913 model).
Multiple paddle switch widths and heights included to get the perfect fit for a variety of handgun models.
Multi-fuel operation; SL-B9® Li-Ion rechargeable battery pack or CR123A.
High-power LED for extreme brightness.
Ambidextrous operation.
One-handed snap on and tighten interface keeps hands away from muzzle when attaching or detaching.
Securely fits a broad range of weapons.
Extensively live fire tested.
Operating temperature: -40°F to +120°F (CR123A) or -4°F to +120°F (SL-B9®).
IPX7-rated design; waterproof to 1 meter for 30 minutes.
Serialized for positive identification.

APPROVALS:

Meets applicable United Kingdom and European Community Directives

CEC Compliant (USB model only)

TAA Compliant

WARRANTY:

Streamlight's Limited Lifetime Warranty

OPTIONAL**ACCESSORIES:**

USB-C charge cord, SL-B9® Li-Ion battery bank charger

FITMENT GUIDE:

1913 Model (59100 & 59101)	Please refer to Streamlight's Fit Guide for the current compatibility list
1913 Slim (59102 & 59103)	Glock® 43X® MOS, 48 MOS, 43X® Rail, and 48 Rail, FN Reflex®, FN Reflex® XL
P365XL (59104 & 59105)	Sig Sauer® P365® and P365® XL (Closed rail systems only - does not fit P365® XMACRO)

All Rights Reserved. GLOCK® and 43X® are registered trademarks of Glock, Inc. FN REFLEX® is a registered trademark of FN Herstal S.A. SIG SAUER® and P365® are registered trademarks of SIG Sauer, Inc. Streamlight has not sought endorsement of this product from Glock, Inc., FN Herstal S.A., or SIG Sauer, Inc. BOROFLOAT® is a registered trademark of SCHOTT AG.

Issued: 12/17/2025

Revised:

Rev:

Built in the USA of U.S. and Foreign Parts.

Document #446