



POLYTAC® 1X USB / POLYTAC® 1X COMPACT, MULTI-FUEL, HANDHELD TACTICAL FLASHLIGHT

DESCRIPTION:	The Streamlight PolyTac® 1X is a compact, tactical flashlight built for durability and performance in extreme conditions. This multi-fuel flashlight offers unmatched versatility, operating on a Streamlight SL-B9® protected Li-Ion USB rechargeable battery pack, CR123A lithium disposable battery, or a AA alkaline/lithium battery. Designed with a rugged polymer body and rocky stipple grip texture for secure handling, the PolyTac® 1X includes a two-way pocket clip for convenient carry and a TEN-TAP® programmable tail switch for customizable lighting modes. Ideal for law enforcement, military, industrial professionals, outdoor enthusiasts, and everyday carry (EDC), this high-performance flashlight delivers reliable illumination when you need it most.		
CASE MATERIAL:	High-impact, super tough nylon polymer for exceptional durability and a sure grip. All openings O-ring sealed. Available in black or yellow.		
DIMENSIONS:	Length: 4.71 in (11.96 cm)	Body Diameter: 1.00 in (2.54 cm)	Head Diameter: 1.22 in (3.10 cm)
		Major Diameter: 1.35 in (3.43 cm)	
WEIGHT:	CR123: 2.93 oz (83.1g)	SL-B9®: 3.03 oz (85.9g)	AA: 3.20 oz (90.7g)
LENS:	High-temperature, impact-resistant BOROFLOAT® glass.		
LIGHT SOURCE:	White LED, impervious to shock with a 50,000-hour lifetime.		
LIGHT OUTPUT:	See charts for specific battery type.		
RUN TIME:	See charts for specific battery type. All claims to 10% of initial lumen output.		
ON/OFF:	Multi-function, push-button tactical tail switch. TEN-TAP® programming allows for user selection of one of three different programs: high/strobe/low (factory default), high only, or low/high.		
BATTERY:	CR123A: One (1) 3-volt CR123A lithium battery with a storage life of 10 years. SL-B9®: One (1) Streamlight Li-Ion 850mAh USB-C rechargeable battery pack with integrated safety circuit, rechargeable up to 500 cycles. Charges within 2.5 hours via optional USB-C cord or bank charger. AA: One (1) alkaline AA battery or one (1) lithium AA battery. WARNING - EXPLOSION RISK, BURN AND FIRE HAZARD. Do not use an SL-B9® battery in firefighting apparatus or fire situations. Do not expose SL-B9® battery to temperatures greater than 140°F (60°C).		
FEATURES:	  High-power LED for extreme brightness. Multi-fuel; accepts a Streamlight SL-B9® battery pack, CR123A battery, or AA battery. IPX7 rated design; waterproof to 1 meter for 30 minutes. 3-meter impact resistance tested. Rocky stipple grip texture for superior grip. TEN-TAP® programmable switch allows for user selection of one of three different programs. Removable two-way pocket clip. Serialized for positive identification.		
APPROVALS:	  Meets applicable United Kingdom and European Community Directives.		
TAA:	Trade Agreement Act Compliant.		
	 CEC Compliant (USB model only).		
WARRANTY:	Streamlight's Limited Lifetime Warranty		
ACCESSORIES:	Colored flip lenses, USB-C charge cords, SL-B9® Li-Ion battery bank charger, holster, safety wand		

CR123A Lithium Battery

	FL1 STANDARD	HIGH	LOW
	350 LUMENS	40 LUMENS	
	1.5h	14h	
	219m	63m	
	12,000cd	1,000cd	

Strobe Run Time: 2.25h

SL-B9® USB Battery Pack

	FL1 STANDARD	HIGH	LOW
	500 LUMENS	40 LUMENS	
	1h	8h	
	268m	63m	

Strobe Run Time: 1.75h

AA Battery

	FL1 STANDARD	HIGH	LOW
	150 LUMENS	40 LUMENS	
	5h	14h	
	141m	63m	

Strobe Run Time: 7h

All performance claims tested to ANSI/PLATO FL1-2019 Standard.
 All rights reserved. BOROFLOAT® is a registered trademark of SCHOTT AG.

Issued: 12/12/2025

Revised:

Rev:

Built in the USA of U.S. and Foreign Parts.

Document #449