



PRODUCT FACT SHEET

PORTABLE SCENE LIGHT III

RUGGED ALL-WEATHER RECHARGEABLE LIGHTING SOLUTION

DESCRIPTION:	The Portable Scene Light III is a rugged, waterproof high-lumen portable lighting solution built for demanding job sites and emergency scenes. Twelve LEDs with wide-pattern reflectors deliver a uniform beam for maximum coverage, ideal for illuminating construction sites, maintenance areas, military operations, and first responder scenes. Three brightness levels allow it to adapt to any environment. Its light head rotates 360° and pivots 180° providing full positioning control. An available wireless remote controls all functions from up to 75 feet away and is pairable with multiple scene lights for simultaneous use. Simple pairing supports multiple remotes or replacement remotes. Its modular design allows use with or without the heavy-duty tripod. Power options include swappable batteries with a dedicated charger, AC power supply or DC power source, making it ideal for indoor and outdoor operations. Battery packs feature illuminated charge level indicators. The Portable Scene Light III pairs with a heavy-duty tripod that allows height extension to 7.7 feet with two intermediate locking positions, providing precise height adjustment for optimal scene illumination. Reversible spiked feet ensure a secure footing on soft terrain while maintaining stability on hard surfaces. Integrated tripod cradles store extra batteries, a corded power supply, and the wireless remote. A built-in carry handle supports easy transport and rapid deployment, making this tripod light well suited for demanding environments. Tripod has 3/8" -16 female threads, adaptable for cameras and camera accessories.
CASE MATERIAL:	Housing: High-impact thermoplastic. Gasket sealed. Tripod: Steel and aluminum.
DIMENSIONS:	Head: Length: 7.5 in. (19.1 cm) Width: 7 in. (17.8 cm) Height: 9 in. (22.9 cm) Tripod collapsed: Length: 9.5 in. (24.1 cm) Width: 9 in. (22.8 cm) Height: 37.9 in. (96.3 cm) Tripod collapsed with head attached: Height: 47.5 in. (120.65 cm) Tripod extended with head attached: Flat feet height: 100 in. (254.0 cm) Tripod minimum footprint required: 44 in. (111.8 cm) *Spiked feet add 2.75 in. (7.0 cm) to height measurements
WEIGHT:	Head: 7.5 lbs. (3.4 kg) with included battery Tripod: 13.8 lbs. (6.2 kg) Total: 21.3 lbs. (9.7 kg)
LENS:	Unbreakable polycarbonate lens with scratch-resistant coating. O-ring sealed.
LIGHT SOURCE:	Twelve (12) high-power LEDs, impervious to shock with a 50,000 hour lifetime.
LIGHT OUTPUT:	See chart. Twelve (12) wide pattern parabolic reflectors produce 10,000 lumens in a smooth pattern. Optimized electronics provide fully regulated intensity.
ON/OFF:	Multi-function toggle switch and/or wireless remote operation features three (3) intensity adjustments and on/off.
RUN TIME:	See chart for battery operated run time. Continuous operation & battery charging supported when operating with included AC power supply or 12VDC power cord.
BATTERY:	One (1) SL-P6® 7.26V, 14.55Ahr, 105.63Whr lithium-ion battery pack with on-board safety control circuit, rechargeable over 1,000 times. System fully recharges in 5 hours in the charger or 7 hours in light when connected to power and the light is turned off. Battery will charge at a reduced rate when operating the light and using power supply.

FEATURES:

Rugged design intended for all-weather outdoor use.

IPX7-rated with battery installed; waterproof to 1 meter for 30 minutes.

IPX4-rated without battery installed.

Swappable battery pack with integrated illuminated battery charge level indicator.

Battery pack charges in the light or in the dedicated charger.

Indefinite run time on AC or DC external power with supplied cords.

7.7' tripod elevates lighting above the scene.

Light weight modular light-head can be used with or without heavy-duty tripod.

Last mode memory returns to the most recent setting used (high/med/low).

Wireless remote control for easy operation at a distance up to 75 feet.

Reversible spiked tripod feet grip soft ground.

Integrated carry handle for easy transportation.

Serialized for positive identification.

APPROVALS:

BC

CEC Compliant

CEUK

Meets applicable United Kingdom and European Community Directives

NFPA

Battery charger meets requirements of NFPA 1900-11.1.11.2 (2024) mounted in any position.

FCC ID: 2BVJK461038

WARRANTY:

Streamlight's Limited Lifetime Warranty.

OPTIONAL ACCESSORIES:

Tripod, International Tripod Adaptor.

Quick release shoulder strap, heavy-duty shoulder strap.

100VAC, 230VAC or 240VAC power cords and 12VDC (vehicle) charger cords.

SL-P6 battery, SL-P6 battery and charger kit.

Wireless remote.

	HIGH	MEDIUM	LOW
LUMENS	10,000	5,000	2,500
RUNTIME	2h	4h	8h
DISTANCE	696m	494m	390m
CANDELA	121,000	61,000	38,000

