

SL-SIDESADDLE® HAZ-LO® **UNIVERSAL FIT, HARD HAT, HELMET & HAT LIGHT**

DESCRIPTION: The SL-SideSaddle HAZ-LO Intrinsically Safe Helmet Light is a lightweight, hands-free lighting solution engineered for hazardous locations and demanding industrial environments. Designed to mount securely on hard hats, safety helmets, and bump caps, it works without interfering with face shields, visors, hearing protection, or other personal protective equipment (PPE). Featuring dual ultra-bright LEDs with spot, flood, and combined spot/flood beam modes, it provides versatile illumination for inspections, maintenance tasks, confined space work, construction projects, and low-light industrial operations. A blue rear safety taillight improves worker visibility. Powered by three AAA batteries, the SL-SideSaddle HAZ-LO delivers dependable portable lighting for professionals.

CASE MATERIAL: Tough polycarbonate thermoplastic construction. Class I, Division 1 models available in high-visibility yellow.

DIMENSIONS: Length: 3 in (7.6 cm) Width: 2.25 in (5.7 cm) Height: 1.14 in (2.9 cm)

WEIGHT: 3.4 oz (95 grams) (with included batteries)

LENS: Unbreakable polycarbonate lens.

LIGHT SOURCE: Dual LEDs, impervious to shock with a 50,000-hour lifetime.

LIGHT OUTPUT: See chart.

ON / OFF: Push-button tail switch with blue rear LED safety taillight.

RUN TIME: See chart.

BATTERY: Three (3) AAA alkaline batteries.

FEATURES: Intrinsically safe.



Universal fit for hard hats, helmets and bump caps.
Does not interfere with most hard hat or helmet accessories.
Conveniently adjustable for personalized beam placement.
Easily removeable for handheld use and battery changes.
IPX7-rated design; waterproof to 1 meter for 30 minutes. All openings O-ring sealed.
2-meter impact resistance tested.
Ultra bright blue LED safety taillight for enhanced visibility.
Spot, flood, and combination optics for application specific illumination.

APPROVALS:  Meets applicable United Kingdom and European Community Directives
Class I, Division 1, Groups A, B, C, D; T4; Class II, Division 1, Groups E, F, G; T-Code: T° 155; Class III
(approved for use with Energizer E92, Rayovac NO.824, and Panasonic LR03XJ)

WARRANTY: Streamlight's Limited Lifetime Warranty

OPTIONAL ACCESSORIES: Hard Hat Mounting Base, Universal Y-Straps, Slotted Hard Hat Straps, Hat Mount Kit

	ANSI PLATO FL1	COMBO	SPOT	FLOOD
OUTPUT	 MAX	250 LUMENS	200 LUMENS	160 LUMENS
RUNTIME		5.25h	5.25h	5.25h
DISTANCE		66m	96m	26m
INTENSITY		1,100cd	2,300cd	170cd