

SURVIVOR PIVOT® DUAL-BEAM, 90-DEGREE ARTICULATING FLASHLIGHT


DESCRIPTION	ORANGE w/o MAGNET	YELLOW w/o MAGNET	ORANGE with MAGNET	YELLOW with MAGNET
Survivor Pivot - 120V/100V AC/12V DC - C1D1	91802	91812	91830	91831
Survivor Pivot - Alkaline - C1D1	91800	91810	91825	91826

Spot, Flood, and Combo Modes in Both High and Low:
Spot:

High: 300 lumens; 369m beam distance; runs 4.25 hrs (Li-Ion); runs 5.5 hrs (alk)
 Low: 70 lumens; 184m beam distance; runs 16 hrs (Li-Ion); runs 15 hrs (alk)

Flood:

High: 300 lumens; 35m beam distance; runs 4.25 hours (Li-Ion); runs 5.5 hrs (alk)
 Low: 70 lumens; 17m beam distance; runs 16 hrs (Li-Ion); runs 15 hrs (alk)

Combo:

High: 325 lumens; 276m beam distance; runs 3.75 hrs (Li-Ion); runs 4.5 hrs (alk)
 Low: 80 lumens; 141m beam distance; runs 13 hrs (Li-Ion); runs 12 hrs (alk)

Weight:

Non-Magnet: 16.2 oz (459 g) w/ Li-ion; 16.7 oz (473 g) w/ alkaline
 Magnet: 17.6 oz (499 g) w/ Li-ion; 18.1 oz (513 g) w/ alkaline

Height: 7.93 in. (20.1 cm)

Width: 2.86 in. (7.26 cm)

Thickness: 3.29 in. (8.36 cm) w/o magnet; 3.64 in. (9.25 cm) with magnet

- Multi-function light featuring a dual-beam and 90-degree articulating head
- Rugged nylon polymer body is virtually indestructible
- Battery status indicator in switch: green when fully charged, red when battery is low and flashes red when only 15 minutes of battery left
- Spring-loaded clip attaches to belts and harnesses; D-ring provides forward-hanging orientation
- Class I, II, Division 1, Groups A, B, C, D, E, F, G; Class III, T-Code: T3/T4 (**Pending approval**)
- IP67-rated; dust-tight and waterproof to 1m for 30 minutes; 2m impact resistance tested
- Charging rack meets requirements of NFPA 1900-11.1.11.2 (2024) mounted in any position
- Flashlight meets 500°F requirements of NFPA 1971-8.6 (2018)

SURVIVOR PIVOT® USB DUAL-BEAM, 90-DEGREE ARTICULATING FLASHLIGHT


DESCRIPTION	ORANGE w/o MAGNET	YELLOW w/o MAGNET	ORANGE with MAGNET	YELLOW with MAGNET
Survivor Pivot USB - C1D2	91804	91814	91838	91839

Spot, Flood, and Combo Modes in Both High and Low:
Spot:

High: 300 lumens; 369m beam distance; runs 4.25 hrs
 Low: 70 lumens; 184m beam distance; runs 16 hrs

Flood:

High: 300 lumens; 35m beam distance; runs 4.25 hours
 Low: 70 lumens; 17m beam distance; runs 16 hrs

Combo:

High: 325 lumens; 276m beam distance; runs 3.75 hrs
 Low: 80 lumens; 141m beam distance; runs 13 hrs

Weight:

Non-Magnet: 15.8 oz (448 g)
 Magnet: 17.2 oz (488 g)

Height: 7.93 in. (20.1 cm)

Width: 2.86 in. (7.26 cm)

Thickness: 3.29 in. (8.36 cm) w/o magnet; 3.64 in. (9.25 cm) with magnet

- Multi-function light featuring a dual-beam and 90-degree articulating head
- Multi-fuel; includes rechargeable SL-B26® battery pack; also accepts (3) AA alkaline batteries
- Rugged nylon polymer body is virtually indestructible
- Battery status indicator in switch: green when fully charged, red when battery is low and flashes red when only 15 minutes of battery left
- Spring-loaded clip attaches to belts and harnesses; D-ring provides forward-hanging orientation
- Class I, II, Division 2, Groups A, B, C, D, F, G; Class III, T-Code: T4 (**Pending approval**)
- IP67-rated; dust-tight and waterproof to 1m for 30 minutes; 2m impact resistance tested
- Charging rack meets requirements of NFPA 1900-11.1.11.2 (2024) mounted in any position
- Flashlight meets 500°F requirements of NFPA 1971-8.6 (2018)

E-SPOT® LITEBOX® // E-SPOT® FIREBOX® RECHARGEABLE , HIGH-CANDELA LANTERN



SYSTEM	E-SPOT LITEBOX ORANGE	E-SPOT LITEBOX YELLOW	E-SPOT FIREBOX ORANGE
Standard System - 120V/100V AC/12V DC	45851	45871	45861
Vehicle Mount System - 12V DC	45855	45875	45865
Power Failure System - 120V AC/12V DC	45857	---	---
Light Only (without charger)	45856	45876	45882



- Choose between high and low modes:
 - High: 1,500 lumens; 110,000 candela; 663m beam; runs 7.5 hours
 - Low: 350 lumens; 25,000 candela; 316m beam; runs 17.75 hours
- Four LEDs with deep parabolic reflectors for a long-range, focused beam pattern
 - Two ultra-bright blue taillight LEDs make certain you can be seen even in thick smoke (FireBox models only)
- Large push-button switch with battery status indicator
- Lithium-ion battery recharges in 5 hours
- High-impact, super-tough nylon construction; reinforced D-rings
- Rubberized cushioned grip handle designed for easy hand-offs; flat base area allows light to stand on its own for scene lighting
- Charging rack meets requirements of NFPA 1900-11.1.11.2 (2024) mounted in any position
- 11.2 in. (28.4 cm); 3.1 lbs. (1389 g)

E-FLOOD® LITEBOX® // E-FLOOD® FIREBOX® RECHARGEABLE LED LANTERN



SYSTEM	E-FLOOD LITEBOX ORANGE	E-FLOOD LITEBOX YELLOW	E-FLOOD FIREBOX ORANGE
Standard System - 120V/100V AC/12V DC	45801	45821	45811
Vehicle Mount System - 12V DC	45805	45825	45815
Power Failure System - 120V AC/12V DC	45807	---	---
Light Only (without charger)	45806	45826	45832



- Choose between high and low modes:
 - High: 1,500 lumens; 4,700 candela; 137m beam; runs 7.5 hours
 - Low: 350 lumens; 1,000 candela; 63m beam; runs 17.75 hours
- Four LEDs with shallow reflectors for a widened beam pattern;
 - Two ultra-bright blue taillight LEDs make certain you can be seen even in thick smoke (FireBox models only)
- Large push-button switch with battery status indicator
- Lithium-ion battery recharges in 5 hours
- High-impact, super-tough nylon construction; reinforced D-Rings
- Rubberized cushioned grip handle designed for easy hand-offs; flat base area allows light to stand on its own for scene lighting
- Charging rack meets requirements of NFPA 1900-11.1.11.2 (2024) mounted in any position
- 11.2 in. (28.4 cm); 3.1 lbs. (1389 g)

BEARTRAP® 360 RECHARGEABLE, MULTI-FUNCTION WORK LIGHT WITH ROTATING BODY



BearTrap 360 - 120V/100V AC - Red 61523
 BearTrap 360 - Int'l (230V/240V) AC - Red 61524

- Features a 360° rotating and 270° pivoting body
- Cool white light with spot and flood modes, each with high, medium, and low modes:
 - Flood fills your work area with evenly dispersed, bright light: High: 2,000 lumens; runs 2.5 hours
 - Spot provides a concentrated beam: High: 1,000 lumens; runs 4.5 hours
- Rechargeable; continues to charge while plugged in and in use
- Clamps virtually anywhere
- Lithium-ion battery recharges in 5.5 hours
- Tough thermoplastic construction with rubberized grip to prevent scratches
- Chemical-resistant lens – withstands most common automotive chemicals
- IPX4-rated; water resistant; 1m impact resistance tested
- 7.62 in. (19.35 cm); 2 lbs. 5 oz (1049 g)

VULCAN CLUTCH® MULTI-FUNCTION, RECHARGEABLE , HIGH-LUMEN LANTERN



SYSTEM	ORANGE WITH QUICK RELEASE STRAP	YELLOW WITH HEAVY DUTY STRAP
Standard System - 120V/100V AC/12V DC	44361	44371
Vehicle Mount System - 12V DC	44365	44375
Light Only (without charger)	44360	44370

- Features a 340° articulating head and 20° downcast head for footpath lighting
- High and low modes:
 - High: 1,700 lumens; 520m beam; runs 6.5 hours
 - Low: 380 lumens; 245m beam; runs 18 hours
- Versatile clamping handle
- Lithium-ion battery recharges in 5 hours
- High-impact, super-tough nylon body; head constructed from high-grade aluminum encased in super-tough nylon
- IP67-rated; dust-tight and waterproof to 1meter for 30 minutes
- 9.39 in. (23.85 cm); 2.84 lbs. (1.288 kg)