

**BEARTRAP®** RECHARGEABLE, MULTI-FUNCTION WORKLIGHT


BearTrap - 120V/100V AC - Red.....	61520
BearTrap - Int'l (230V/240V) AC - Red.....	61521

- Cool white light with spot and flood modes, each with high, medium and low modes:
  - Flood fills your work area with evenly dispersed, bright light: High: 2,000 lumens; runs 2.5 hours
  - Spot provides a concentrated beam: High: 1,000 lumens; runs 4.5 hours
- Rechargeable, continues to charge while plugged in and in use
- Clamps virtually anywhere
- Lithium ion battery recharges in 5.5 hours
- Tough thermoplastic construction with rubberized grip to prevent scratches; Chemical-resistant lens - withstands most common automotive chemicals
- IPX4 water resistant; 1m impact resistance tested

**VANTAGE® II** ULTRA-COMPACT HELMET MOUNTED LIGHT


Vantage II - Fire helmet mount and with lithium battery – Box.....	#69331
Vantage II - Gallet helmet mount and with lithium battery – Box.....	#69332
Vantage II - Industrial hard hat mount and with lithium battery – Box.....	#69333

- High and low modes:
  - High: 350 lumens; 118m beam; runs 2.25 hours
  - Low: 135 lumens; 80m beam; runs 5 hours
- Bright blue taillight LED ensures you can be seen even from behind
- Durable, anodized aluminum construction; IPX7 waterproof to 1m for 30 minutes
- Includes one CR123A lithium battery, integrated mount and hex key
- 2.37" (6.01 cm); 3.65 oz. (103.5g)
- Meets requirements of NFPA 1971-8.6 (2013)

**VULCAN® 180 HAZ-LO® // VULCAN® 180** MULTI-FUNCTION PORTABLE SCENE LIGHT


SYSTEM	HAZ-LO ORANGE	HAZ-LO YELLOW	DIV 2 ORANGE	DIV 2 YELLOW
Vulcan 180 Standard System - 120V/100V AC/12V DC	44331	44321	44311	44307
Vulcan 180 Vehicle Mount System - 12V DC	44335	44325	44315	44305
Vulcan 180 without charger	44330	44320	44310	44300

**HAZ-LO® intrinsically safe model:**

- High: 400 lumens; 316m beam; runs 10 hours
- Low: 130 lumens; 128m beam; runs 24 hours
- Class I, Div. 1 Groups A,B,C,D,E,F,G; Class I Zone 0, Groups IIC, Class III; T-Code: T4
- Meets requirements of NFPA 1901-14.1.10.2 (2016) mounted in any position


**DIV 2 model:**

- High: 1,200 lumens; 548m beam; runs 5.75 hours
- Low: 350 lumens; 296m beam; runs 16 hours
- Class I, Div. 2, Groups A, B, C, D; Class II, Division 2, Groups F, G; Class III; Temperature Class T4
- Meets requirements of NFPA 1901-14.1.10.2 (2016) mounted in any position

- Features a 180° articulating head
- Three LEDs produce a tight beam with optimum peripheral illumination; ultra-bright blue taillight LEDs make certain you can be seen even in thick smoke
- Rechargeable lithium ion battery
- High impact, super-tough nylon construction; articulating head constructed from high grade aluminum encased in super-tough nylon; reinforced D-Rings
- Rubberized cushioned-grip handle designed for easy hand off; flat base area allows light to stand on its own for scene lighting
- 7.43 in. (18.8 cm); 2.45 lbs. (1112g)





## SL-B26<sup>®</sup> PROTECTED LITHIUM ION BATTERY PACK & BANK CHARGER

ITEM	SINGLE BATTERY	2-PACK
SL-B26 Battery Pack	#22101	#22102

### BATTERY FEATURES:

- Protected lithium ion battery with on-board safety control circuit
- USB rechargeable; also charges in charger holder
- Charges in 5 hours using USB cord
- 2.75 in (7.0 cm); 1.7 oz (48 grams)



ITEM	W/O BATTERIES	W/ BATTERIES
8-Unit Bank Charger - 120V/100V AC	#20221	#20224
8-Unit Bank Charger - 12V DC	#20220	#20223

### 8-UNIT CHARGER FEATURES:

- Organize, store and charge up to eight lithium ion USB rechargeable battery packs; charge time: 5.25 hours
- Charge bays securely hold batteries in place - ideal for truck mounting
- Charge indicators over each battery slot: red = charging, green = charged
- Low-profile - 1" (2.54 cm) - minimal mounting area required
- Impact-resistant polymer construction
- 10.45" x 4.74" x 1" (26.54x12.06x2.54 cm); 7.6 oz. (216g) w/o batteries; 20.88 oz. (592g) w/ batteries
- Meets requirements of NFPA 1901-14.1.10.2 (2016) mounted in upright position





## POLYTAC<sup>®</sup> 90 X USB // POLYTAC<sup>®</sup> 90 X RIGHT-ANGLE MULTI-FUNCTION FLASHLIGHT



SYSTEM	BLACK	YELLOW	ORANGE	ORANGE W/ GEAR KEEPER
PolyTac 90X with CR123A lithium batteries	88830	88831	88834	88832
PolyTac 90X USB - SL-B26 battery pack & USB cord	88835	88836	88838	88837

- MULTI-FUEL - uses one Streamlight SL-B26™ protected Li-Ion USB rechargeable battery pack; also accepts two CR123A lithium batteries
- High and low modes:
  - High for a super-bright spot beam: 500 lumens; 167m beam; runs 2.5 hours (CR123A); runs 3.75 hours (SL-B26 battery pack)
  - Low for a less intense beam and longer run time: 85 lumens; 64m beam; runs 12 hours (CR123A); runs 19 hours (SL-B26 battery pack)
- Multi-function push-button head switch easy to use with gloved hands
  - Features battery life indicator
- High-impact, “super-tough” nylon polymer construction
  - Integrated carabiner style D-ring for a variety of attachment methods
  - Multi-position pocket clip attaches to turnout gear, harnesses, etc.; offers a variety of mounting positions
- IPX7 waterproof to 1m for 30 minutes
- Gear Keeper option helps prevent loss; Tether features spectra nylon line with 36” extension; 6 oz. retraction force
- 4.43” (11.25 cm); 4.8 oz. (136g) with (SL-B26 battery pack); 4.3 oz. (122g) with CR123A lithium batteries
- Meets requirements of NFPA 1971-8.6 (2018)



## VANTAGE<sup>®</sup> 180 X USB // VANTAGE<sup>®</sup> 180 X HELMET/RIGHT-ANGLE MULTI-FUNCTION FLASHLIGHT



SYSTEM	ORANGE	BLACK
Vantage 180 X with CR123A lithium batteries	88901	88903
Vantage 180 X USB - SL-B26 battery pack & USB cord	88911	88913

- MULTI-FUEL - uses one Streamlight SL-B26™ protected Li-Ion USB rechargeable battery pack; also accepts two CR123A lithium batteries
- High and low modes:
  - High for a super-bright spot beam: 250 lumens; 170m beam; runs 4 hours (CR123A); runs 5 hours (SL-B26 battery pack)
  - Low for a less intense beam and longer run time: 100 lumens; 103m beam; runs 12 hours (CR123A); runs 15 hours (SL-B26 battery pack)
- Blue LED (helmet mount use) for visibility in heavy smoke; white LED for a downcast flood light to see what’s at your feet (right-angle light)
- Head articulates 180° to aim the beam
- Use as a helmet light; fits both traditional and modern style helmets; no tools necessary to quickly remove for use as a handheld flashlight
- Use as a right-angle light; forward facing spot light with downcast light
- High-impact, “super-tough” chemical-resistant nylon polymer construction; integrated stainless steel multi-function clip; turnout gear attachment hook; IPX7 waterproof to 1m for 30 minutes; 1m impact resistance tested
- 5.2” (13.20 cm); 5.5 oz. (156g)
- Meets requirements of NFPA 1971-8.6 (2013)



## PROTAC<sup>®</sup> 90 X USB // PROTAC<sup>®</sup> 90 X ULTRA-COMPACT, RIGHT ANGLE TACTICAL LIGHT



ProTac 90 X - CR123A lithium batteries and holster.....	#88094
ProTac 90 X USB - SL-B26 battery pack and holster.....	#88095

- Multi-Fuel -Uses one Streamlight SL-B26™ protected Li-Ion USB rechargeable battery pack; also accepts two CR123A lithium batteries
- High, medium, low and strobe modes:
  - High: 1,000 lumens; 171m beam; runs 2.5 hours (CR123A); runs 1.75 hours (SL-B26 battery pack)
  - Medium: 300 lumens; 91m beam; runs 4 hours (CR123A); runs 4.75 hours (SL-B26 battery pack)
  - Low: 65 lumens; 42m beam; runs 21 hours (CR123A); runs 24 hours (SL-B26 battery pack)
  - Strobe runs 2.5 hours (C123A); runs 3.5 hours (SL-B26 battery pack)
- TEN-TAP<sup>®</sup> Programming - choose from three different operating programs: 1) high/strobe/low 2) high only 3) low/medium/high
- Multi-function push-button head switch easy to use with gloved hands
- Removable pocket clip attaches to MOLLE, turnout gear, harnesses, etc.
- Durable, anodized aluminum construction with impact-resistant glass lens; IPX7 waterproof to 1m for 30 minutes
- 4.39” (11.1 cm); 4.9 oz. (139g) with (SL-B26 battery pack); 4.4 oz. (125g) with CR123A lithium batteries

## PORTABLE SCENE LIGHT II RECHARGEABLE HIGH LUMEN SCENE LIGHT



Portable Scene Light II - 120V AC/DC ..... #46000

- Produces a high lumen flood pattern
- Five intensity levels correspond to desired run time
 

	100%	80%	60%	40%	20%
<b>LUMENS:</b>	10,000	8,300	6,300	4,500	2,300
<b>RUN TIME:</b>	2h	2.75h	3.75h	5.75h	11h
- Multi-level illumination for scene lighting; head swivels 360° to aim the beam where you need it
  - Stackable for “light tower” capability
- Lithium ion batteries charge in 6 hours
  - Batteries will continue to charge while in use when plugged in; runs indefinitely using AC or DC power cord
- Waterproof to 1m for 30 minutes
- High-impact, thermoplastic housing mounted in a virtually indestructible alloy steel frame
- Compact size (16x11x12 in; 40.6x28.9x30.5 cm); 15.38 lbs. (6.1 kg)



## PORTABLE SCENE LIGHT PORTABLE, RECHARGEABLE SCENE LIGHT



PORTABLE SCENE LIGHT CONFIGURATION	PSL	PSL EXT
Portable Scene Light with 120V AC/12V DC and shoulder strap	#45670	#45680

- Produces a uniform flood pattern; selectable diffuser settings for two beam widths; three user-selectable outputs:
  - High for a super-bright flood beam: 5,300 lumens; 410m beam; runs 4 hours
  - Medium for an intense beam and longer run time: 2,500 lumens; 292m beam; runs 9 hours
  - Low for when a less intense beam is ideal and for longer run times: 1,300 lumens; 215m beam; runs 18 hours
- Optimum peripheral illumination for scene lighting; head swivels 90° to aim the beam where you need it for task lighting
- Sealed lead acid batteries will charge while in use and plugged into a power source; runs indefinitely using AC or DC power cord
- Balanced design and easy setup; less than 30 seconds for full deployment; pole extends to 72”
- IP67 rated; dust-tight and waterproof to 1m for 30 minutes
- Designed to resist 40mph wind continuous in all directions with head fully extended
- Portable Scene Light: 25 lbs (11.3 kg); packs to a compact size (22”; 55.88 cm) for easy stowage
- Portable Scene Light Ext: 25.5 lbs (11.6 kg); Packs to a compact size (25.5”; 64.8 cm) for easy stowage

## SURVIVOR® LOW PROFILE, RIGHT ANGLE FLASHLIGHT



120V/100V AC/12V DC - Orange ..... #90503  
 Alkaline Model - Orange ..... #90540

- High, low, moonlight and flash modes:
  - High: 175 lumens; 405m beam; runs 3.5 hours (rech); runs 4 hours (alkaline)
  - Low: 60 lumens; 237m beam; runs 13 hours (rech); runs 15 hours (alkaline)
  - Moonlight provides a low-level light when battery life is essential: runs for 20 days
  - Flash mode: runs for 8 hours
- Custom designed optic with optional, interchangeable Smoke-Cutter® plugs for preferred beam pattern:
  - ~ Black plug significantly reduces peripheral light for a tighter beam
  - ~ Amber plug reduces peripheral light and eye fatigue caused by glare
- Constructed of high impact, super-tough nylon; IPX4 water-resistant; 2m impact-resistance tested; low-profile bezel minimizes snag hazards
- Spring-loaded clip attaches to belts and harnesses; D-ring provides forward hanging orientation
- Uses rechargeable battery pack; also accepts four “AA” alkaline batteries
- Class I, II, Division 1, Groups C, D, E, F, G; Class III, T-Code: T4; Class I, Division 2, Groups A, B, C, D; T-Code: T4
- Charger meets requirements of NFPA 1901-14.1.10.2 (2016) mounted in any position
- Flashlight meets 500°F requirements of NFPA 1971-8.6 (2013)

## VANTAGE® HELMET MOUNTED LIGHT



Vantage - Black with blue taillight LED ..... #69140

- Lightweight, compact, low profile design easily attaches above or below brim on fire helmets; fits both traditional and modern style helmets
- 115 lumens; 167m beam distance; runs 6 hours
- Ultra-bright taillight LED ensures you’ll be seen even from behind
- Anodized aluminum construction; chemical-resistant polymer LED housing with reflective strip; IPX7 waterproof to 1m for 30 minutes
- Uses two CR123A lithium batteries (included)
- Meets requirements of NFPA 1971-8.6 (2013)