



# IECEX Certificate of Conformity

## INTERNATIONAL ELECTROTECHNICAL COMMISSION IEC Certification System for Explosive Atmospheres

for rules and details of the IECEx Scheme visit [www.iecex.com](http://www.iecex.com)

Certificate No.: **IECEX LC 25.0010X** Page 1 of 4 [Certificate history:](#)  
Status: **Current** Issue No: 1 [Issue 0 \(2025-12-05\)](#)  
Date of Issue: 2026-04-24  
Applicant: **Streamlight Inc.**  
30 Eagleville Road  
Eagleville, PA 19403  
**United States of America**  
Equipment: **Dualie Rechargeable**  
Optional accessory:  
Type of Protection: **Ex ia op is**  
Marking: **Ex ia op is IIC T4 Ga**  
Battery powered, 3.6V, 3450mAhdc (1 cell rechargeable Lithium-ion Battery), peaks of 20mAdc  
-20°C ≤ Ta ≤ 40°C

Approved for issue on behalf of the IECEx  
Certification Body:

**Kavinder Dhillon, P.L.Eng.**

Position:

**Certification Manager**

Signature:  
(for printed version)

Date:  
(for printed version)

1. This certificate and schedule may only be reproduced in full.
2. This certificate is not transferable and remains the property of the issuing body.
3. The Status and authenticity of this certificate may be verified by visiting [www.iecex.com](http://www.iecex.com) or use of this QR Code.



Certificate issued by:

**LabTest Certification Inc.**  
205 - 8291 92 Street  
Delta, British Columbia  
V4G 0A4  
Canada





# IECEX Certificate of Conformity

Certificate No.: **IECEX LC 25.0010X**

Page 2 of 4

Date of issue: 2026-04-24

Issue No: 1

Manufacturer: **Streamlight Inc.**  
30 Eagleville Road  
Eagleville, PA 19403  
**United States of America**

Manufacturing  
locations:

This certificate is issued as verification that a sample(s), representative of production, was assessed and tested and found to comply with the IEC Standard list below and that the manufacturer's quality system, relating to the Ex products covered by this certificate, was assessed and found to comply with the IECEX Quality system requirements. This certificate is granted subject to the conditions as set out in IECEX Scheme Rules, IECEX 02 and Operational Documents as amended

## STANDARDS :

The equipment and any acceptable variations to it specified in the schedule of this certificate and the identified documents, was found to comply with the following standards

[IEC 60079-0:2017](#) Explosive atmospheres - Part 0: Equipment - General requirements  
Edition:7.0

[IEC 60079-11:2011](#) Explosive atmospheres - Part 11: Equipment protection by intrinsic safety "i"  
Edition:6.0

[IEC 60079-28:2015](#) Explosive atmospheres - Part 28: Protection of equipment and transmission systems using optical radiation  
Edition:2

This Certificate **does not** indicate compliance with safety and performance requirements other than those expressly included in the Standards listed above.

## TEST & ASSESSMENT REPORTS:

A sample(s) of the equipment listed has successfully met the examination and test requirements as recorded in:

Test Reports:

[CA/LC/ExTR25.0010/00](#)

[CA/LC/ExTR25.0010/01](#)

Quality Assessment Report:

[NO/NEM/QAR14.0001/07](#)



# IECEX Certificate of Conformity

Certificate No.: **IECEX LC 25.0010X**

Page 3 of 4

Date of issue: 2026-04-24

Issue No: 1

## **EQUIPMENT:**

Equipment and systems covered by this Certificate are as follows:

The product is a portable, battery operated, hand-held flashlight. The product is an intrinsically safe apparatus. The product comprises a lantern body (red or yellow or black static dissipative plastic), a face cap (black plastic) and two switches (black rubber). Inside of the equipment there is a 3.6V rechargeable Lithium-ion Battery cell and max. four printed circuit boards.. There are no input or output IS terminals. There is a terminal for charging the battery, which is not used in hazardous locations (explosive atmosphere).

Dimension: cylinder design - length cca. 17.7cm , diameter of body cca 3.7cm, diameter of face cap part 4.5cm

## **SPECIFIC CONDITIONS OF USE: YES as shown below:**

1. Do not open in a hazardous area.
2. Use only Streamlight battery 68792.
3. The magnetic clip model contains attached external conductive parts. The measured capacitance on the magnets is 12pF. User shall determine suitability for the specific application.
4. Charge only with Streamlight charger.



# IECEX Certificate of Conformity

Certificate No.: **IECEX LC 25.0010X**

Page 4 of 4

Date of issue: 2026-04-24

Issue No: 1

**DETAILS OF CERTIFICATE CHANGES (for issues 1 and above)**

To correct a typo error.