



Optional Magnetic Clip for convenient placement and access

NON-MAGNET OPTION PICTURED



MAGNET OPTION PICTURED



Dual-beam for optimal illumination

Material/Lens Impact and chemical resistant Engineered Polymer resin; v-ring sealed and vented; gasket sealed and vented. Class I, Division 1 models available in high visibility yellow or black.

Dims/Weight

	STANDARD CLIP		MAGNETIC CLIP	
IMPERIAL	LENGTH: 7 in	BODY THICKNESS: 1.06 in	LENGTH: 7.5 in	BODY THICKNESS: 1.06 in
	BODY WIDTH: 1.52 in	FACE CAP DIAMETER: 1.86 in	BODY WIDTH: 1.52 in	FACE CAP DIAMETER: 1.86 in
	WEIGHT (WITH ALK BATTERIES): 6.8 oz		WEIGHT (WITH ALK BATTERIES): 7.1 oz	
	WEIGHT (WITH LITHIUM BATTERIES): 5.9 oz		WEIGHT (WITH LITHIUM BATTERIES): 6.2 oz	
METRIC	LENGTH: 19.1 cm	BODY THICKNESS: 2.69 cm	LENGTH: 17.78 cm	BODY THICKNESS: 2.69 cm
	BODY WIDTH: 3.86 cm	FACE CAP DIAMETER: 4.72 cm	BODY WIDTH: 3.86 cm	FACE CAP DIAMETER: 4.72 cm
	WEIGHT (WITH ALK BATTERIES): 193 g		WEIGHT (WITH ALK BATTERIES): 201 g	
	WEIGHT (WITH LITHIUM BATTERIES): 167 g		WEIGHT (WITH LITHIUM BATTERIES): 176 g	

Light Source/ Output Two (2) White LEDs, impervious to shock with a 50,000 hour lifetime.

	SPOT	FLOOD	COMBINED
LUMENS	140	140	245
CANDELA	7,300	8	---
DISTANCE	171 m	8 m	---
RUN TIME	18 hours	18 hours	9 hours

Switch Opposing head switches for easy identification. Spot LED push-button head switch provides one handed momentary or "constant on" operation. Flood LED push button head switch provides on/off operation.

Battery Three (3) "AA" size alkaline or lithium primary batteries. Mechanical battery polarity protection.

- Features**
- Dual function with opposing switches for easy function identification
 - IP67-rated; dust-tight and waterproof to 1 meter for 30 minutes; 2m impact resistance tested
 - Spot beam utilizes smooth parabolic reflector for tight beam with optimum peripheral illumination
 - Integrated, spring loaded belt clip contained within body outline
 - Corrosion proof

Approvals Class I, II, Division 1, Groups A, B, C, D, E, F, G; Class III; CL I, ZN 0, IIC; Exia; T-Code: T4. MSHA Permissible Handheld Flashlight. Approval No. 20-A160001-0. Tested for Intrinsic Safety in Methane-Air mixtures only. Charge or replace batteries in fresh air only. II 1G Ex ia op is IIC T3/T4 Ga; FTZU 15ATEX0221X, IECEx FTZU 16.0017X. Meets applicable European Community Directives. * See product for specific ratings. All performance claims to ANSI/PLATO FL1-2016 Standard

Warranty Streamlight warrants this product to be free of defects for a lifetime of use except for batteries and bulbs, abuse and normal wear. We will repair, replace or refund the purchase price of this product should we determine it to be defective. This limited lifetime warranty also excludes rechargeable batteries, chargers, switches and electronics which have a 2 year warranty with proof of purchase. THIS IS THE ONLY WARRANTY, EXPRESSED OR IMPLIED, INCLUDING ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. INCIDENTAL, CONSEQUENTIAL OR SPECIAL DAMAGES ARE EXPRESSLY DISCLAIMED EXCEPT WHERE SUCH LIMITATION IS PROHIBITED BY LAW. You may have other specific legal rights which vary by jurisdiction. Visit streamlight.com for full warranty information.

Description	YELLOW		BLACK	
	UPC	Item #	UPC	Item #
Dualie 3AA - 3 "AA" alkaline batteries - Clam	080926-68750-9	68750	080926-68752-3	68752
Dualie 3AA - 3 "AA" alkaline batteries, magnetic clip and lanyard - Box	080926-68782-0	68782	080926-68783-7	68783
Dualie 3AA - without batteries - Mailer	080926-68751-6	68751	080926-68753-0	68753
Dualie 3AA - without batteries, magnetic clip and lanyard - Box	080926-68780-6	68780	080926-68781-3	68781

	Description	UPC	Item #
	4AA/3AA Helmet Mount	080926-68085-2	68085
	4AA/3AA Gallet mount	080926-68086-9	68086
	Poly Mount Kit	080926-68089-0	68089
	Rubber Helmet Strap	080926-99075-3	99075