

# ENDURO® PRO

LOW PROFILE, HIGH-PERFORMANCE, MULTI-FUNCTION HEADLAMP



Model available with rubber strap and 3M<sup>®</sup> Dual Lock<sup>®</sup> fasteners for use on hard hats

Two red LEDs (yellow model) or green LEDs (coyote model)



Spot LED



Available Colors:



A low-profile, multi-function headlamp with the performance you've come to expect from Streamlight. Three lighting modes to cover a variety of tasks: spot beam for a focused beam, flood for soft area illumination that won't tire your eyes and red or green LEDs to preserve night vision.

OUTPUT						
0011 01	SPOT			FLOOD		
	HIGH	MEDIUM	LOW	HIGH	MEDIUM	LOW
LUMENS	200	75	25	135	45	15
CANDELA	2,250	835	300	210	80	20
DISTANCE	95m	57m	35m	29m	18m	9m
RUN TIME	6 hrs	14 hrs	38 hrs	6 hrs	14 hrs	38 hrs

### **ITEM NUMBERS**

Description	UPC	Item#
Enduro Pro - Includes (3) AAA alkaline batteries, elastic headstrap - Clam - Yellow	080926-61420-8	61420
Enduro Pro - Includes (3) AAA alkaline batteries, elastic headstrap - Box - Yellow	080926-61421-5	61421
Enduro Pro - Includes (3) AAA alkaline batteries, elastic headstrap - Clam - Coyote	080926-61425-3	61425
Enduro Pro - Includes (3) AAA alkaline batteries, elastic headstrap, rubber hard hat strap and 3M® Dual Lock® - Box - Yellow	080926-61422-2	61422

#### **KEY FEATURES**

- · Lightweight, low-profile design
- 45° tilting head, especially handy for reading
- Multi-fuction, push-button switch easy to use with gloves
- Yellow model features two red LEDs for low light visibility and the coyote model features two green LEDs

#### **BATTERY**

 Uses three AAA alkaline batteries (included); also accepts AAA lithium batteries

## MATERIAL/DURABILITY

- Tough, polycarbonate thermoplastic construction with elastomer over mold
- Unbreakable polycarbonate lenses
- IPX4 water-resistant
- 2m impact resistance tested

#### **DIMENSIONS**

**LENGTH:** 2.19 in (5.56 cm)

**WEIGHT:** 3.4 oz (96.38g) w/alkaline // 3 oz (85.04g) w/lithium

## **WARRANTY**

Limited lifetime warranty Visit streamlight.com for full warranty information