



ENDURO® PRO HAZ-LO® ATEX



LOW-PROFILE, ZONE 0 RATED MULTI-FUNCTION HEADLAMP



Model available with rubber strap and 3M® Dual Lock® fasteners for use on hard hats



Flood LED
Spot LED



Available Colors:



A light-weight, low-profile, Zone 0 rated headlamp. Three lighting modes cover a variety of tasks: spot for a focused beam, flood for soft area illumination that won't tire your eyes and spot/flood combo for even more light output.

OUTPUT

	COMBO	SPOT	FLOOD
LUMENS	235	160	160
CANDELA	---	1,320	100
DISTANCE	---	73m	20m
RUN TIME	4.75 hrs	5 hrs	5 hrs

ITEM NUMBERS

Description	UPC	Item #
Enduro Pro HAZ-LO (ATEX) - Includes (3) AAA alkaline batteries, elastic and rubber hard hat straps and (1) 3M® Dual Lock® Rechargeable Fastener - Red	080926-61428-4	61428
Enduro Pro HAZ-LO (InMetro) - Includes (3) AAA alkaline batteries, elastic and rubber hard hat straps and (1) 3M® Dual Lock® Rechargeable Fastener - Red	080926-61423-9	61423

ACCESSORIES

Description	UPC	Item #
Rubber Hard Hat Strap - <i>no image available</i>	080926-61426-8	61426

KEY FEATURES

- Three modes: spot/flood combo for increased light output, spot for distance, flood for area illumination
- 45° tilting head, especially handy for reading
- Multi-function, push-button switch easy to use with gloves

BATTERY

- Uses three AAA alkaline batteries (included)

MATERIAL/DURABILITY

- Tough, polycarbonate thermoplastic construction with elastomer over mold
- Unbreakable polycarbonate lenses; recessed to prevent scratches
- IP67 waterproof to 1 meter for 30 minutes
- 2-meter impact resistance tested

DIMENSIONS

LENGTH: 5.56 cm

WEIGHT: 99.2g
W/ BATTERIES

RATINGS

- ATEX: II 1G Ex ia op is IIC T4 Ga – FTZU 18 ATEX 0101X
- IECEx: Ex ia op is IIC T4 Ga - IECEx FTZU 19.0003
- InMetro: Ex is op is IIC T4 Ga DNV 20.0025 X

WARRANTY

Limited lifetime warranty
Visit streamlight.com for full warranty information