



PROTAC® RAIL MOUNT 1L-X // PROTAC® RAIL MOUNT 1L-X PRO

MULTI-FUEL TACTICAL LIGHT FOR SHORT-BARRELED RIFLES,
CARBINES AND SUBMACHINE GUNS



ProTac Rail Mount 1L-X model uses
a standard push button tail switch



ProTac Rail Mount 1L-X Pro model

Available Colors:



The ProTac® Rail Mount 1L-X is a compact, multi-fuel, high-output tactical light designed for short-barreled rifles, carbines, and submachine guns. Powered by one (1) Streamlight SL-B9® rechargeable lithium-ion battery pack or one (1) CR123A battery, this tactical light delivers high lumen output for superior visibility in low-light environments.

OUTPUT

	SL-B9		CR123A	
	HIGH	LOW	HIGH	LOW
LUMENS	850	100	500	100
CANDELA	30,000	3,400	18,000	3,400
DISTANCE	346m	117m	268m	117m
RUN TIME	30 mins	4.5 hrs	1.75 hrs	6.5 hrs

Strobe runs 1.25 hours (SL-B9); runs 2.5 hours (CR123A)

ITEM NUMBERS

Description	UPC	Item #
ProTac Rail Mount 1L-X - Includes tailcap switch, mounting hardware, M-LOK® mount and (1) CR123A lithium battery - Black	080926-89026-8	89026
ProTac Rail Mount 1L-X Pro - Includes Jack Cap®, M-LOK® Kit, Momentary Switch, Hardware Kit, 2.5 mm Allen Wrench and (1) CR123A lithium battery - Black	080926-89024-4	89024
ProTac Rail Mount 1L-X USB - Includes tailcap switch, mounting hardware, M-LOK® mount and (1) SL-B9 battery pack and USB cord - Black	080926-89027-5	89027
ProTac Rail Mount 1L-X USB Pro - Includes Jack Cap®, M-LOK® Kit, Momentary Switch, Hardware Kit, 2.5 mm Allen Wrench, (1) SL-B9 battery pack and USB cord - Black	080926-89025-1	89025

KEY FEATURES

- **ProTac Rail Mount 1L-X Pro:** Uses Jack-Cap® tailcap switch that offers operational switch redundancy with push-button operation or remote pressure switch operation
- **ProTac Rail Mount 1L-X:** Uses a standard push button tail switch for ease of activation without a pressure pad
- TEN-TAP® Programmable
- MIL-STD-1913 Picatinny rail and M-LOK® mounts included

BATTERY

- **Multi-Fuel:** Uses one Streamlight SL-B9 lithium-ion rechargeable battery pack
- Also accepts one CR123A lithium battery

MATERIAL/DURABILITY

- 6000 series machined aircraft aluminum with anodized finish
- Gasket-sealed glass lens
- **ProTac Rail Mount 1L-X Pro Model:** IP67-rated with standard push-button switch installed (waterproof to 1m for 30 minutes); IP54-rated with remote pressure switch installed (water-resistant)
- **ProTac Rail Mount 1L-X Model:** IP67-rated; waterproof to 1m for 30 minutes

DIMENSIONS

LENGTH: 4.64 in (11.79 cm)

WEIGHT: CR123A 5.5 oz (155.9g) // SL-B9 5.6 oz (158.8g)

WARRANTY

Limited lifetime warranty
Visit streamlight.com for full warranty information

ACCESSORIES

	Description	UPC	Item #
	M-LOK® Mount	080926-88300-0	88300
	Jack-Cap®	080926-88130-3	88130
	Remote Retaining Clips	080926-88178-5	88178
	Straight Latching Pressure Switch	080926-89008-4	89008
	Straight Momentary Pressure Switch	080926-69135-3	69135
	CR123A Lithium Batteries - 2 Pack	080926-85175-7	85175
	CR123A Lithium Batteries - 6 Pack	080926-85180-1	85180
	CR123A Lithium Batteries - 12 Pack	080926-85177-1	85177
	CR123A Lithium Batteries - 400 Pack	080926-85179-5	85179
	SL-B9 Battery Pack - 2pk	080926-20237-5	20237
	SL-B9 Battery Pack - 8pk	080926-20238-2	20238
	SL-B9 Battery Pack - 100pk	080926-20239-9	20239
 <i>Batteries not included</i>	8-unit SL-B9 Bank Charger - 120V100V AC	080926-20231-3	20231
	8-unit SL-B9 Bank Charger - 230/240V AC	080926-20232-0	20232
	8-unit SL-B9 Bank Charger - 12V DC	080926-20230-6	20230
 <i>Batteries included</i>	8-unit SL-B9 Bank Charger - 120V100V AC	080926-20234-4	20234
	8-unit SL-B9 Bank Charger - 230/240V AC	080926-20235-1	20235
	8-unit SL-B9 Bank Charger - 12V DC	080926-20233-7	20233
	USB-C cord	080926-22084-3	22084
	USB-C “Y” cord	080926-22090-4	22090

M-LOK® is a registered trademark of Magpul Industries Corp. All rights reserved. BOROFLOAT® is a registered trademark of SCHOTT AG.