



Case Material/ Machined aircraft-grade aluminum with type II anodized finish. Available in black.

Lens: Unbreakable polycarbonate lens with scratch-resistant coating. O-ring sealed

Dimensions/ 13.1 in. (33.3 cm) Diameter: Major Diameter: 2.50 in. (6.35 cm)

Weight: 1.7 lb. (.77 kg) with battery

Light Source: White LED technology, impervious to shock with a 50,000 hour lifetime. Deep-dish parabolic reflector produces a tight beam with optimal peripheral illumination to aid in navigation

Light Output/ High: 60,000 candela peak beam intensity; 350 lumens; runs 2 hours

Run time: Medium: 27,000 candela peak beam intensity; 160 lumens; runs 4 hours

Low: 1,000 candela peak beam intensity; 10 lumens; runs 50 hours

Strobe: runs 4 hours

On/Off: Multi-function, push-button barrel switch. One handed operation of momentary, variable intensity or strobe mode

Battery: 5-cell, 6.0 Volt Ni-MH sub-C battery, rechargeable up to 1000 times

Charging: Illuminated switch housing indicates charge status; steady for charging and blinking for charging complete. 7 hour battery recharge time. Fits existing charger-holders, available with AC or 12V DC charge cords.

Features: IPX4 rated design; water-resistant

1 meter impact resistance tested

Serialized for positive identification

Approvals: Meets applicable European Community directives.

Warranty: Streamlight warrants this product to be free of defects for a lifetime of use except for batteries and bulbs, abuse and normal wear. We will repair, replace or refund the purchase price of this product should we determine it to be defective. This limited lifetime warranty also excludes rechargeable batteries, chargers, switches and electronics which have a 2 year warranty with proof of purchase. **THIS IS THE ONLY WARRANTY, EXPRESSED OR IMPLIED, INCLUDING ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. INCIDENTAL, CONSEQUENTIAL OR SPECIAL DAMAGES ARE EXPRESSLY DISCLAIMED EXCEPT WHERE SUCH LIMITATION IS PROHIBITED BY LAW.** You may have other specific legal rights which vary by jurisdiction.

Item	UPC	Item #
SL-20L - 230V AC/12V DC - 2 Sleeves NiMH	080926-20705-9	20705
SL-20L - 240V AC/12V DC - 2 Sleeves NiMH	080926-20707-3	20707
SL-20L - 120V AC/12V DC Smart Charge - 2 Sleeves NiCd	080926-20603-8	20603
SL-20L - 120V AC/12V DC Smart Charge - 2 Sleeves NiMH	080926-20703-5	20703
SL-20L - 100V AC/12V DC - 2 Sleeves NiMH	080926-20709-7	20709
SL-20L - 230V AC NiMH	080926-20704-2	20704
SL-20L - 240V AC NiMH	080926-20706-6	20706
SL-20L - 120V AC Smart Charge NiCd	080926-20601-4	20601
SL-20L - 120V AC Smart Charge NiMH	080926-20701-1	20701
SL-20L - 100V AC NiMH	080926-20708-1	20708
SL-20L - 12V DC Smart Charge NiMH	080926-20702-8	20702
SL-20L NiMH - (WITHOUT CHARGER)	080926-20700-4	20700



-Item		UPC	Part #
Charge Sleeve Assembly (Cord not included)		080926-22047-8	22047
DC2 direct wire charge cord		080926-22050-8	22050
DC1 Charge Cord		080926-22051-5	22051
100V/120V AC charge cord		080926-22060-7	22060
230V AC charge cord		080926-22061-4	22061
AC Plug 240V		080926-22062-1	22062
5 Unit Bank Charger, 120V		080926-21400-2	21400
5 Unit Bank Charger DC		080926-21401-9	21401
Battery Stick (NiMH)		080926-77375-2	77375
Safety Wand	Red	080926-22511-4	22511
Safety Wand	Blue	080926-22512-1	22512
Safety Wand	Glow in the Dark	080926-22513-8	22513
Safety Wand	White	080926-22517-6	22517
Safety Wand	Yellow	080926-22519-0	22519
Ring Holder		080926-22911-2	22911
Holster, SL Series (Nylon)		080926-25090-1	25090

