



# SURVIVOR<sup>®</sup> ATEX

ATEX RATED RIGHT-ANGLE FLASHLIGHT



Spring-loaded clip with built in D-ring  
Rubber dome push-button switch



Available Colors:

The Survivor ATEX features a low-profile bezel that doesn't interfere with gear or equipment. Its multi-fuel capability makes it easily interchangeable with different battery types. Lightweight design, because we understand that every ounce counts. Zone 0 gas and Zone 20 dust rated.

## KEY FEATURES

- Rubber dome push-button switch, easy to use with gloves
- Super strong, spring-loaded gear clip securely grabs onto turnout gear
- Specialized optic combines low profile with strong performance and wide beam

## OUTPUT

|                                  | HIGH    | LOW    |
|----------------------------------|---------|--------|
| LUMENS                           | 175     | 60     |
| CANDELA                          | 41,000  | 14,000 |
| DISTANCE                         | 405m    | 237m   |
| RUN TIME <small>Li-Ion</small>   | 3.5 hrs | 10 hrs |
| RUN TIME <small>Alkaline</small> | 8 hrs   | 20 hrs |

Flash for signaling runs 5 hrs  
Moonlight mode provides low-level lighting for battery conservation: runs 15 days

## ITEM NUMBERS

| Description                        | UPC            | Item # |
|------------------------------------|----------------|--------|
| Survivor ATEX - 230V AC/12V DC     | 080926-90562-7 | 90562  |
| Survivor InMetro - 230V AC/12V DC  | 080926-90580-1 | 90580  |
| Survivor ATEX - 240V AC/12V DC     | 080926-90563-4 | 90563  |
| Survivor ATEX - 100V AC/12V DC     | 080926-90564-1 | 90564  |
| Survivor ATEX - Without Charger    | 080926-90566-5 | 90566  |
| Survivor InMetro - Without Charger | 080926-90581-8 | 90581  |
| Survivor ATEX - Alkaline           | 080926-90567-2 | 90567  |
| Survivor InMetro - Alkaline        | 080926-90582-5 | 90582  |

## BATTERY

- Multiple power sources
- 6.2V, 1.5 Ah lithium-ion battery, rechargeable up to 1,500 times
- Optional four AA alkaline or four AA lithium batteries (requires battery carrier)

## MATERIAL/DURABILITY

- Housing, base and battery made from high-impact, rugged nylon polymer body which is virtually indestructible
- Unbreakable polycarbonate lens with silicone anti-scratch coating
- One-way valve for case venting
- IP66 dust-tight and water-resistant
- 2m impact resistance tested

## DIMENSIONS

HEIGHT: 17.9 cm

WEIGHT: LI-ION or ALKALINE 388g // AA LITHIUM 354g  
W/ BATTERIES

## SAFETY RATINGS

- Ex: II 1G Ex ia op is IIB T3/T4 Ga; II 2G Ex ia op is IIC T3/T4 Gb FTZU 15 ATEX 0046X
- Ex: Ex ia op is IIB T3/T4 Ga; Ex ia op is IIC T3/T4 Gb IECEX FTZU 15.0029X
- InMetro: Ex ia op is IIB T3/T4 Ga; Ex ia op is IIC T3/T4 Gb DNV 16.0014X
- Charger meets requirements of NFPA 1900-11.1.11.2 (2024) mounted in any position
- Flashlight meets 500°F requirements of NFPA 1970-14.2 (2025)

## WARRANTY

Limited lifetime warranty  
Visit [streamlight.com](http://streamlight.com) for full warranty information

## ACCESSORIES

|   | Description  | UPC  | Item #                  |
|---|--|--|-------------------------|
|    | 5-Unit 120V AC Bank Charger<br>5-Unit 230V AC Bank Charger<br>5-Unit 12V DC Bank Charger | 080926-90910-6<br>080926-90911-3<br>080926-90912-0 | 90910<br>90911<br>90912 |
|    | Battery Carrier (for alkaline models)<br><i>Batteries not included</i>                   | 080926-90542-9                                     | 90542                   |
|    | Charger Holder   | 080926-90345-6                                     | 90345                   |
|    | Lithium-ion Battery Pack   | 080926-90316-8                                     | 90316                   |
|    | 240V AC (AUS/NZ) Charge Cord   | 080926-22048-5                                     | 22048                   |
|    | 12V DC2 Charge Cord  | 080926-22050-8                                     | 22050                   |
|  | 12V DC1 Charge Cord  | 080926-22051-5                                     | 22051                   |
|  | 120V AC Charge Cord  | 080926-22060-7                                     | 22060                   |
|  | 230V AC Charge Cord  | 080926-22061-4                                     | 22061                   |
|  | 240V UK AC Charge Cord   | 080926-22062-1                                     | 22062                   |
|  | Smoke Cutter Plug Kit  | --   | 908019                  |
| No Image Available  | 24 Volt Direct Wire to 12 Volt Charge Converter  | 080926-22093-3                                     | 22093                   |