



SURVIVOR PIVOT® ATEX ZONE 0 ARTICULATING RIGHT-ANGLE FLASHLIGHT



Pictured without magnet option



Pictured with magnet option

Material/Lens: Housing, base, and battery housing made from high-impact, super tough polymer offering exceptional durability. Spring-loaded clip with built-in D-ring easily attaches to belts and harnesses and reduces unwanted rotation. One-way valve for case venting. Available in international safety orange.

IMPERIAL	HEIGHT:	7.93 in	WIDTH:	2.86 in	THICKNESS:	3.29 in	THICKNESS w/ MAGNET:	3.64 in
	WEIGHT w/o MAGNET LI-ION:	16.2 oz	WEIGHT w/o MAGNET ALKALINE:	16.7 oz	WEIGHT w/ MAGNET LI-ION:	17.6 oz	WEIGHT w/ MAGNET ALKALINE:	18.1 oz
METRIC	HEIGHT:	20.14 cm	WIDTH:	7.26 cm	THICKNESS:	8.36 cm	THICKNESS w/ MAGNET:	9.25 cm
	WEIGHT w/o MAGNET LI-ION:	459 g	WEIGHT w/o MAGNET ALKALINE:	473 g	WEIGHT w/ MAGNET LI-ION:	499 g	WEIGHT w/ MAGNET ALKALINE:	513 g

Light Source: Spot: Custom "Total Internal Reflection" (TIR) optic for narrow beam and optimum peripheral illumination
Flood: Unique bias reflector provides maximum area illumination

Output/ Run Time:	COMBO		SPOT		FLOOD	
	HIGH	LOW	HIGH	LOW	HIGH	LOW
LUMENS:	325	80	300	70	300	70
CANDELA:	19,000	5,000	34,000	8,500	300	75
DISTANCE:	276 m	141 m	369 m	184 m	35 m	17 m
RUN TIME LI-ION:	3.75 hours	13 hours	4.25 hours	16 hours	4.25 hours	16 hours
RUN TIME ALKALINE:	4.5 hours	12 hours	5.5 hours	15 hours	5.5 hours	15 hours

Switch: Ultrasonic welded switch designed for extremely long life. Rubber dome push-button actuator provides easy operation, even when wearing heavy gloves. Translucent switch boot contains an integrated red/green battery status indicator
 - Solid green for 5 seconds: Light is charged and ready for use
 - Solid red: 45 minutes or less of battery life remaining
 - Flashing red: 15 minutes or less of battery life remaining

Battery: - 2.6 Ahr Li-Ion battery pack fully charges in 5 hours. Battery status indicator shows red when charging; turns green when fully charged.
 - Three (3) optional AA alkaline batteries

Features: - Simultaneous spot and flood mode for maximum illumination
 - Translucent switch boot with integrated battery status indicator
 - Charge cradle designed for one-handed light removal
 - Multi-fuel design; accepts multiple battery types
 - IP67 rated; dust-tight and waterproof to 1m for 30 minutes; 2m impact resistance tested
 - Strong spring-loaded clip grabs onto belts and gear
 - Magnet option

Approvals: SGSNA24ATEX012901; IECEx SNA 24.0001
 II 1G Ex ia op is IIC T3/T4 Ga
 T-CLASS T4: Duracell MN1500, Varta 4006, Energizer EN91
 T-CLASS T3: Streamlight pack 90340

Flashlight meets 500°F requirements of NFPA 1971-8.6 (2018).
 Charger meets requirements of NFPA 1900-11.1.11.2 (2024) mounted in any position.
 Meets applicable European Community Directives.

Warranty: Streamlight warrants this product to be free of defects for a lifetime of use except for batteries and bulbs, abuse and normal wear. We will repair, replace, or refund the purchase price of this product should we determine it to be defective. This limited lifetime warranty also excludes rechargeable batteries, chargers, switches, and electronics which have a 2-year warranty with proof of purchase. THIS IS THE ONLY WARRANTY, EXPRESSED OR IMPLIED, INCLUDING ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. INCIDENTAL, CONSEQUENTIAL, OR SPECIAL DAMAGES ARE EXPRESSLY DISCLAIMED EXCEPT WHERE SUCH LIMITATION IS PROHIBITED BY LAW. You may have other specific legal rights which vary by jurisdiction. Visit streamlight.com for full warranty information.

Description	UPC	Item #	Description	UPC	Item #
Survivor Pivot ATEX - 230V AC/12V DC - Orange	080926-91823-8	91823	Survivor Pivot ATEX Magnet - 230V AC/12V DC - Orange	080926-91836-8	91836
Survivor Pivot ATEX - 240V AC/12V DC - Orange	080926-91824-5	91824	Survivor Pivot ATEX Magnet - 240V AC/12V DC - Orange	080926-91837-5	91837
Survivor Pivot ATEX - 100/12V DC - Orange	080926-91822-1	91822	Survivor Pivot ATEX Magnet - 100/12V DC - Orange	080926-91835-1	91835
Survivor Pivot ATEX - Alkaline - Orange	080926-91820-7	91820	Survivor Pivot ATEX Magnet - Alkaline - Orange	080926-91827-6	91827

Note: The Survivor Pivot® ATEX is not compatible with legacy Survivor® chargers.

	Description	UPC	Item #
	5-Unit 120V AC Bank Charger	080926-90910-6	90910
	5-Unit 230V AC Bank Charger	080926-90911-3	90911
	5-Unit 12V DC Bank Charger	080926-90912-0	90912
	Charger Holder	080926-90345-6	90345
	Battery Carrier (for alkaline or SL-B26® models) <i>Batteries not included</i>	080926-90342-5	90342
	Lithium-Ion Battery Pack - ATEX	080926-90340-0	90340
	12V DC1 Charge Cord	080926-22051-5	22051
	12V DC2 Charge Cord	080926-22050-8	22050
	120V AC Charge Cord	080926-22060-7	22060
	230V AC Charge Cord	080926-22061-4	22061
	240V AC Charge Cord	080926-22062-1	22062
	Magnet Accessory Kit (<i>magnet only, clip not included</i>) - Survivor Pivot	080926-91840-5	91840