

## SURVIVOR PIVOT® USB **BUDGET-FRIENDLY** ARTICULATING RIGHT-ANGLE FLASHLIGHT







Pictured without magnet option

Pictured with magnet option

Material/Lens:

Housing, base, and battery housing made from high-impact, super tough polymer offering exceptional durability. Spring-loaded clip with built-in D-ring easily attaches to belts and harnesses and reduces unwanted rotation. One-way valve for case venting. Available in orange and high-visibility yellow.

Dims/Weight:

IMPERIAI		<b>HEIGHT:</b> 7.93 in	<b>WIDTH:</b> 2.86 in	THICKNESS: 3.29 in	THICKNESS w/ magnet: 3.64 in	
IIVIFE	EKIAL	WEIGHT W/O MAGNET SL-B26: 15.8 OZ	WEIGHT W/O MAGNET ALKALINE: 16.7 OZ	WEIGHT w/ magnet sl-b26: 17.2 oz	WEIGHT w/ magnet alkaline: 18.1 oz	
METRI	.DIC	<b>HEIGHT</b> : 20.14 cm	<b>WIDTH:</b> 7.26 cm	THICKNESS: 8.36 cm	THICKNESS w/ magnet: 9.25 cm	
IVIE		WEIGHT w/o magnet sl-b26: 448 g	WEIGHT w/o magnet alkaline: 473 g	WEIGHT w/ magnet sl-b26: 488 g	WEIGHT w/ magnet alkaline: 513 g	

Light Source:

Spot: Custom "Total Internal Reflection" (TIR) optic for narrow beam and optimum peripheral illumination Flood: Unique bias reflector provides maximum area illumination

Output/ Run Time:

	COMBO		SPOT		FLOOD	
	HIGH	LOW	HIGH	LOW	HIGH	LOW
LUMENS:	325	80	300	70	300	70
CANDELA:	19,000	5,000	34,000	8,500	300	75
DISTANCE:	276 m	141 m	369 m	184 m	35 m	17 m
RUN TIME (SL-B26):	3.75 hours	13 hours	4.25 hours	16 hours	4.25 hours	16 hours
RUN TIME (ALK):	4.5 hours	12 hours	5.5 hours	15 hours	5.5 hours	15 hours

Switch: Ultrasonic welded switch designed for extremely long life. Rubber dome push-button actuator provides easy operation, even when wearing heavy gloves.

Translucent switch boot contains an integrated red/green battery status indicator

- Solid green for 5 seconds: Light is charged and ready for use
- Solid red: 45 minutes or less of battery life remaining
- Flashing red: 15 minutes or less of battery life remaining

- Battery: One Streamlight SL-B26® protected Li-Ion USB-rechargeable battery pack
  - Three (3) optional AA alkaline batteries

- Features: Simultaneous spot and flood mode for maximum illumination
  - Translucent switch boot with integrated battery status indicator
  - Charge cradle designed for one-handed light removal
  - Multi-fuel design; accepts multiple battery types

- IP67 rated; dust-tight and waterproof to 1m for 30 minutes;
- 2m impact resistance tested
- Strong spring-loaded clip grabs onto belts and gear
- Magnet option

Approvals:

PENDING: Class I & II, Division 2, Groups A, B, C, D, F, G; Class III, T-Code: T4 only with Streamlight 220115

Flashlight meets 500°F requirements of NFPA 1971-8.6 (2018).

CEC Compliant.

Meets applicable United Kingdom and European Community Directives.

Warranty:

Streamlight warrants this product to be free of defects for a lifetime of use except for batteries and bulbs, abuse and normal wear. We will repair, replace, or refund the purchase price of this product should we determine it to be defective. This limited lifetime warranty also excludes rechargeable batteries, chargers, switches, and electronics which have a 2-year warranty with proof of purchase. THIS IS THE ONLY WARRANTY, EXPRESSED OR IMPLIED, INCLUDING ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. INCIDENTAL, CONSEQUENTIAL, OR SPECIAL DAMAGES ARE EXPRESSLY DISCLAIMED EXCEPT WHERE SUCH LIMITATION IS PROHIBITED BY LAW. You may have other specific legal rights which vary by jurisdiction. Visit streamlight.com for full warranty information.

Description	UPC	Item #
Survivor Pivot USB - Orange	080926-91804-7	91804
Survivor Pivot USB - Yellow	080926-91814-6	91814
Survivor Pivot Magnet USB - Orange	080926-91838-2	91838
Survivor Pivot Magnet USB - Yellow	080926-91839-9	91839

	Description	UPC	Item #
	Charger Kit with USB Cord	080926-22010-2	22010
	Charger Kit with 120V AC Adapter	080926-22011-9	22011
	SL-B26 Battery Pack	080926-22101-7	22101
11.	SL-B26 Battery Packs - 2PK	080926-22102-4	22102
	SL-B26 Battery Packs - 8PK	080926-22105-5	22105
	Battery Carrier (for alkaline or SL-B26® models)  Batteries not included	080926-90342-5	90342
	40" (101.6 cm) USB cord	080926-22070-6	22070
	22" (55.88 cm) USB cord	080926-22081-2	22081
20000	8-Unit Bank Charger - batteries not included - 12V DC	080926-20220-7	20220
S TREOMLIGHT.	8-Unit SL-B-26 Bank Charger - batteries not included - 120V/100V AC	080926-20221-4	20221
W 511	8-Unit SL-B-26 Bank Charger - batteries not included - 230V/240V AC	080926-20222-1	20222
Man	8-Unit SL-B26 Bank Charger - battery packs included - 12V DC	080926-20223-8	20223
WWWWW	8-Unit SL-B26 Bank Charger - battery packs included - 120V/100V AC	080926-20224-5	20224
in the second	8-Unit SL-B26 Bank Charger - battery packs included - 230V/240V AC	080926-20225-2	20225
	Magnet Accessory Kit (magnet only, clip not included) - Survivor Pivot	080926-91840-5	91840