



STREAMLIGHT®

SURVIVOR PIVOT®



CLASS I, DIVISION 1 RATED, DUAL-BEAM RECHARGEABLE FLASHLIGHT



Spring-loaded clip
Optional magnet available



Battery status indicator in switch:

- Green indicates full charge
- Turns red when battery is nearing low voltage
- Flashes red continuously when 15 minutes left of battery life



Available Colors:



The multi-function, C1D1 safety-rated Survivor Pivot features a dual beam and 90° articulating head. Its spot beam uses a cool white, high-power LED for maximum distance illumination and its flood beam is angled downward for area illumination.

KEY FEATURES

- 90° articulating head aims the beam where you need it
- Securely locks into charger with quick release latch for one-handed grab and go
- Translucent switch boot with integrated battery status indicator

OUTPUT

	SPOT		FLOOD		COMBO	
	HIGH	LOW	HIGH	LOW	HIGH	LOW
LUMENS	300	70	300	70	325	80
CANDELA	34,000	8,500	300	75	19,000	5,000
DISTANCE	369m	184m	35m	17m	276m	141m
RUN TIME Li-Ion	4.25 hrs	16 hrs	4.25 hrs	16 hrs	3.75 hrs	13 hrs
RUN TIME Alkaline	5.5 hrs	15 hrs	5.5 hrs	15 hrs	4.5 hrs	12 hrs

ITEM NUMBERS

Description	UPC	Item #
Survivor Pivot - 120V/100V AC/12V DC - Orange	080926-91802-3	91802
Survivor Pivot - 230V AC/12V DC - Orange	080926-91803-0	91803
Survivor Pivot - Alkaline - Orange	080926-91800-9	91800
Survivor Pivot - Light Only - Orange	080926-91801-6	91801
Survivor Pivot - 120V/100V AC/12V DC - Yellow	080926-91812-2	91812
Survivor Pivot - 230V AC/12V DC - Yellow	080926-91813-9	91813
Survivor Pivot - Alkaline - Yellow	080926-91810-8	91810
Survivor Pivot - Light Only - Yellow	080926-91811-5	91811

see reverse side for additional item numbers

BATTERY

- 3.4 Ahr rechargeable lithium-ion battery; charges in 5 hours
- Optional three AA alkaline batteries (requires battery carrier)
- Battery status indicator

MATERIAL/DURABILITY

- Housing and base made from high-impact, super tough nylon
- One-way valve for case venting
- IP67 dust-tight and waterproof to 1m for 30 minutes
- 2m impact resistance tested

DIMENSIONS

HEIGHT: 7.93 in (20.14 cm)

WEIGHT: LI-ION 16.2 oz (459g) // ALKALINE 16.7 oz (473g)

WEIGHT: LI-ION 17.6 oz (499g) // ALKALINE 18.1 oz (513g)
W/ MAGNET

SAFETY RATINGS

- Class I & II, Division 1, Groups A, B, C, D, E, F, G;
Class III, T-Code: T3/T4
- Charger meets requirements of NFPA 1900-11.1.11.2 (2024)
mounted in any position

WARRANTY

Limited lifetime warranty
Visit streamlight.com for full warranty information

ITEM NUMBERS

Description	UPC	Item #	Description	UPC	Item #
Survivor Pivot Magnet - 120V/100V AC/12V DC - Orange	080926-91830-6	91830	Survivor Pivot Magnet - 120V/100V AC/12V DC - Yellow	080926-91831-3	91831
Survivor Pivot Magnet - 230V AC/12V DC - Orange	080926-91832-0	91832	Survivor Pivot Magnet - 230V AC/12V DC - Yellow	080926-91833-7	91833
Survivor Pivot Magnet - Alkaline - Orange	080926-91825-2	91825	Survivor Pivot Magnet - Alkaline - Yellow	080926-91826-9	91826
Survivor Pivot Magnet - Light Only - Orange	080926-91828-3	91828	Survivor Pivot Magnet - Light Only - Yellow	080926-91829-0	91829

*Note: The Survivor Pivot is not compatible with legacy Survivor® chargers

ACCESSORIES

	Description	UPC	Item #
	5-Unit 120V AC Bank Charger 5-Unit 230V AC Bank Charger 5-Unit 240V AC Bank Charger 5-Unit 12V DC Bank Charger	080926-90910-6 080926-90911-3 080926-90913-7 080926-90912-0	90910 90911 90913 90912
	Charger Holder	080926-90345-6	90345
	Battery Carrier (for alkaline models) <i>Batteries not included</i>	080926-90342-5	90342
	Lithium-ion Battery Pack - C1D1	080926-90341-8	90341
	12V DC2 Charge Cord	080926-22050-8	22050
	12V DC1 Charge Cord	080926-22051-5	22051
	120V AC Charge Cord	080926-22060-7	22060
	230V AC Charge Cord	080926-22061-4	22061
	240V AC Charge Cord	080926-22062-1	22062
	Magnet Accessory Kit (<i>magnet only, clip not included</i>)	080926-91840-5	91840