



SURVIVOR[®] X ATEX



ZONE 0 AND ZONE 20 ATEX RATED RIGHT-ANGLE FLASHLIGHT



Spring-loaded clip with built in D-ring



Battery status indicator in switch:

- Green indicates full charge
- Solid red when 45 minutes of battery left
- Flashes red continuously when 15 minutes left of battery life



Available Colors:



The Survivor X ATEX provides added features and increased output. Multi-fuel capability makes it easily interchangeable with different battery types. Lightweight design, because we understand that every ounce counts. Zone 0 gas and Zone 20 dust-tight rated.

KEY FEATURES

- Carry more light with less weight
- Rechargeable option with improved charger design
- Multiple options for clipping or hanging on your gear

OUTPUT

	HIGH	LOW
LUMENS	250	60
CANDELA	50,000	14,000
DISTANCE	447m	237m
RUN TIME Li-Ion	3.75 hrs	15 hrs
RUN TIME Alkaline	5 hrs	15 hrs

Flash runs 8 hours

ITEM NUMBERS

Description	UPC	Item #
Survivor X ATEX - 100V AC/12V DC	080926-90972-4	90972
Survivor X ATEX - 230V AC/12V DC	080926-90973-1	90973
Survivor X ATEX - 240V AC/12V DC	080926-90974-8	90974
Survivor X ATEX - Alkaline	080926-90970-2	90970
Survivor X ATEX - Light Only	080926-90971-7	90971
Survivor X InMetro - 230V AC/12V DC	080926-90975-5	90975
Survivor X InMetro - Light Only	080926-90976-2	90976
Survivor X InMetro - Alkaline	080926-90977-9	90977

BATTERY

- 3.3 Ahr rechargeable lithium-ion battery pack; charges in 5 hours
- Optional three AA alkaline batteries (requires battery carrier)
- Battery status indicator

MATERIAL/DURABILITY

- Housing, base and battery housing made from high-impact, rugged nylon polymer which is virtually indestructible
- Spring-loaded clip with built-in D-ring easily attaches to belts and harnesses and reduces unwanted rotation
- One-way valve for case venting
- IP67 dust-tight and waterproof to 1m for 30 minutes

DIMENSIONS

HEIGHT: 17.9 cm

WEIGHT: LI-ION 346g // ALKALINE 363g

RATINGS

- SGS22ATEX0081; BAS22UKEX0222 *Issue 1*; IECEx BAS22.0045 II 1G Ex ia IIC T3/T4 Ga; II 1D Ex ia IIIC T₂₀₀131°C Da
- InMetro: Ex ia IIC T4/T3 Ga; Ex ib IIIB T270°C Db
- Charger meets requirements of NFPA 1900-11.1.11.2 (2024) mounted in any position
- Flashlight meets 500°F requirements of NFPA 1970-14.2 (2025)

WARRANTY

Limited lifetime warranty

Visit streamlight.com for full warranty information

ACCESSORIES

	Description	UPC	Item #
	5-Unit 120V AC Bank Charger	080926-90910-6	90910
	5-Unit 230V AC Bank Charger	080926-90911-3	90911
	5-Unit 240V AC Bank Charger	080926-90913-7	90913
	5-Unit 12V DC Bank Charger	080926-90912-0	90912
	Charger Holder	080926-90345-6	90345
	Battery Carrier (for alkaline models) <i>Batteries not included</i>	080926-90342-5	90342
	Lithium-ion Battery Pack - ATEX	080926-90347-0	90347
	12V DC2 Charge Cord	080926-22050-8	22050
	12V DC1 Charge Cord	080926-22051-5	22051
	120V AC Charge Cord	080926-22060-7	22060
	230V AC Charge Cord	080926-22061-4	22061
	240V AC Charge Cord	080926-22062-1	22062
	24 Volt Direct Wire to 12 Volt Charge Converter	080926-22093-3	22093