



SURVIVOR[®] X USB



BUDGET-FRIENDLY, USB RECHARGEABLE RIGHT-ANGLE FLASHLIGHT



Spring-loaded clip with built in D-ring

- Battery status indicator in switch:
- Green indicates full charge
 - Solid red when 45 minutes of battery left
 - Flashes red continuously when 15 minutes left of battery life



Available Colors:  

The Survivor X USB provides budget-friendly rechargeability combined with added features and increased lumen output. Multi-fuel capability makes it easily interchangeable with different battery types. Lightweight design, because we understand that every ounce counts.

KEY FEATURES

- Carry more light with less weight
- Specialized optic combines low profile with strong performance and a wide beam
- Multiple options for clipping or hanging on your gear

OUTPUT

	HIGH	LOW
LUMENS	250	60
CANDELA	50,000	14,000
DISTANCE	447m	237m
RUN TIME SL-B26	4 hrs	15 hrs
RUN TIME Alkaline	5 hrs	15 hrs

ITEM NUMBERS

Description	UPC	Item #
Survivor X USB - Includes (1) SL-B26 battery pack, USB cord and battery carrier - Orange	080926-90044-8	90044
Survivor X USB - Includes (1) SL-B26 battery pack, USB cord and battery carrier - Yellow	080926-90244-2	90244

BATTERY

- Multi-Fuel: Uses one rechargeable SL-B26[®] lithium-ion battery pack; also accepts three AA alkaline batteries
- SL-B26 battery pack charges in 5 hours
- Battery status indicator

MATERIAL/DURABILITY

- Housing and base made from high-impact, rugged nylon polymer which is virtually indestructible
- Spring-loaded clip with built-in D-ring easily attaches to belts and harnesses and reduces unwanted rotation
- One-way valve for case venting
- IP67 dust-tight and waterproof to 1m for 30 minutes

DIMENSIONS

HEIGHT: 7.06 in (17.9 cm)
WEIGHT: SL-B26 11.9 oz (337g) // ALKALINE 12.8 oz (363g)

SAFETY RATINGS

- Class I & II, Division 2, Groups A, B, C, D, F, G; Class III, T-Code: T4 only with Streamlight 220115
- Flashlight meets 500°F requirements of NFPA 1970-14.2 (2025)

WARRANTY

Limited lifetime warranty
 Visit streamlight.com for full warranty information

ACCESSORIES

	Description	UPC	Item #
	SL-B26 Charger Kit with USB Cord	080926-22010-2	22010
	SL-B26 Charger Kit with 120V AC Adapter	080926-22011-9	22011
	SL-B26 Battery Pack - 1 Pack SL-B26 Battery Pack - 2 Pack SL-B26 Battery Pack - 8 Pack	080926-22101-7 080926-22102-4 080926-22105-5	22101 22102 22105
	Battery Carrier (for alkaline and SL-B26 models) <i>Batteries not included</i>	080926-90342-5	90342
	40" (101.6 cm) USB cord 22" (55.88 cm) USB cord	080926-22070-6 080926-22081-2	22070 22081
 <p>BATTERIES NOT INCLUDED</p>	8-Unit SL-B26 Bank Charger - 12V DC 8-Unit SL-B26 Bank Charger - 120V/100V AC 8-Unit SL-B26 Bank Charger - 230V/240V AC	080926-20220-7 080926-20221-4 080926-20222-1	20220 20221 20222
 <p>BATTERIES INCLUDED</p>	8-Unit SL-B26 Bank Charger - 12V DC 8-Unit SL-B26 Bank Charger - 120V/100V AC 8-Unit SL-B26 Bank Charger - 230V/240V AC	080926-20223-8 080926-20224-5 080926-20225-2	20223 20224 20225
	Smoke Cutter Plug Kit	--	908019