SURVIVOR® X

CLASS I, DIVISION 1 RATED RIGHT-ANGLE FLASHLIGHT

Spring-loaded clip with built in D-ring

Battery status indicator in switch:
- Green indicates full charge
- Solid red when 45 minutes of battery left
- Flashes red continuously when 15 minutes left of battery life

Available Colors:

The Survivor X provides added features and increased output. Multi-fuel capability makes it easily interchangeable with different battery types. Lightweight design, because we understand that every ounce counts. Class 1, Div 1 safety-rated.

KEY FEATURES

- Carry more light with less weight
- Rechargeable option with improved charger design
- Multiple options for clipping or hanging on your gear

OUTPUT

	HIGH	LOW
LUMENS	250	60
CANDELA	50,000	14,000
DISTANCE	447m	237m
RUN TIME Li-Ion	3.75 hrs	15 hrs
RUN TIME Alkaline	5 hrs	15 hrs

ITEM NUMBERS

Description	UPC	Item #
Survivor X - 120V/100V AC/12V DC - Orange	080926-90952-6	90952
Survivor X - 230V AC/12V DC - Orange	080926-90953-3	90953
Survivor X - Alkaline - Orange	080926-90950-2	90950
Survivor X - Light Only - Orange	080926-90951-9	90951
Survivor X - 120V/100V AC/12V DC - Yellow	080926-90962-5	90962
Survivor X - 230V AC/12V DC - Yellow	080926-90963-2	90963
Survivor X - Alkaline - Yellow	080926-90960-1	90960
Survivor X - Light Only - Yellow	080926-90961-8	90961

BATTERY

- 3.4 Ahr rechargeable lithium-ion battery; charges in 5 hours
- Optional three AA alkaline batteries (requires battery carrier)
- Battery status indicator

MATERIAL/DURABILITY

- Housing, base, and battery made from high-impact, super tough nylon
- Spring-loaded clip with built-in D-ring easily attaches to belts and harnesses and reduces unwanted rotation
- One-way valve for case venting
- IP67 dust-tight and waterproof to 1m for 30 minutes

DIMENSIONS

HEIGHT: 7.06 in (17.9 cm)

WEIGHT: LI-ION 12.2 oz (346g) // ALKALINE 12.8 oz (363g)

SAFETY RATINGS

- Class I & II; Division 1; Groups A, B, C, D, E, F, G; Class III, T-Code: T3/T4
- Charger meets requirements of NFPA 1900-11.1.11.2 (2024) mounted in any position
- Flashlight meets 500°F requirements of NFPA 1970 – 14.2 (2025)

WARRANTY

Limited lifetime warranty
Visit streamlight.com for full warranty information

ITEM NUMBERS

	Description	UPC	Item #
	5-Unit 120V AC Bank Charger 5-Unit 230V AC Bank Charger 5-Unit 240V AC Bank Charger 5-Unit 12V DC Bank Charger	080926-90910-6 080926-90911-3 080926-90913-7 080926-90912-0	90910 90911 90913 90912
	Charger Holder	080926-90345-6	90345
	Battery Carrier (for alkaline models) *Batteries not included*	080926-90342-5	90342
	Lithium-ion Battery Pack - C1D1	080926-90341-8	90341
	12V DC2 Charge Cord	080926-22050-8	22050
	12V DC1 Charge Cord	080926-22051-5	22051
	120V AC Charge Cord	080926-22060-7	22060
	230V AC Charge Cord	080926-22061-4	22061
	240V AC Charge Cord	080926-22062-1	22062