


TLR-2 HL® G HIGH LUMEN RAIL MOUNTED FLASHLIGHT WITH GREEN LASER



- Material/Lens** 6000 Series machined aircraft aluminum with black anodized finish. High impact, chemically resistant engineering polymer laser housing. High temperature, shock mounted, impact resistant Boro Float glass
- Dims/Weight** Length: 3.39 in. (8.61 cm); Width: 1.47 in. (3.73 cm) Height: 1.83 in. (4.64 cm) ;4.78 oz (135.5 grams) with batteries (included in purchase)
- Light Source** C4®LED technology, impervious to shock with a 50,000 hour lifetime; 510-530nm direct drive green laser with wide operating temperature range
- Output/Run time** 800 lumens; 15,000 candela peak beam intensity; 245m beam; runs 1.5 hours (Laser/LED simultaneously); Runs 17 hours (Laser only)
Engineered optic produces a concentrated beam with optimum peripheral illumination; Green laser provides high visibility long-range targeting
Solid-state current regulation for consistent illumination level. Laser provides long-range targeting
- Switch** Ambidextrous momentary/steady On-Off switch. Three position Mode Selector switch (Laser only, LED Illumination only, both)
Double tap of momentary paddle within 0.4 seconds activates strobe.
- Battery** Two 3V CR123A lithium batteries
- Features**
- Ambidextrous momentary/steady On-Off switch
 - One handed snap-on/tighten interface keeps hands away from muzzle when attaching/detaching
 - Securely fits a broad range of weapons
 - Mounts directly to handguns with Glock-style rails and to all MIL-STD-1913 (Picatinny) rails
 - Includes keys for Glock-style, Picatinny, Beretta 90two, S&W 99 and S&W TSW
 - Extensively live-fire tested impact resistant construction
 - Windage and Elevation adjustment screws mounted in brass bushings for long life and dependable zero retention.
 - Highly accurate sight repeatability when remounting.
 - Operating temperature: -40°F to +120°F.
 - IPX4 water resistant
- Approvals** Most models meet applicable European Community Directives
- Warranty** Streamlight warrants this product to be free of defects for a lifetime of use except for batteries and bulbs, abuse and normal wear. We will repair, replace or refund the purchase price of this product should we determine it to be defective. This limited lifetime warranty also excludes rechargeable batteries, chargers, switches and electronics which have a 2 year warranty with proof of purchase. **THIS IS THE ONLY WARRANTY, EXPRESSED OR IMPLIED, INCLUDING ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. INCIDENTAL, CONSEQUENTIAL OR SPECIAL DAMAGES ARE EXPRESSLY DISCLAIMED EXCEPT WHERE SUCH LIMITATION IS PROHIBITED BY LAW.** You may have other specific legal rights which vary by jurisdiction.

Item	UPC	Part #
TLR-2 HLG Includes Rail Locating Keys for Glock style, 1913 Picatinny, S&W 99/TSW, and Beretta 90two. Lithium batteries. Boxed.	0890926-69265-7	69265

Designed and Assembled in the USA



Item	UPC	Part #
Vertical Grip with Rail - Machined aluminum, hard anodized ambidextrous rail grabber vertical foregrip with integral Picatinny rail and storage compartment	080926-69114-8	69114
Flip Lens	080926-69115-5	69115
Flip Lens	080926-69116-2	69116
Flip Lens	080926-69117-9	69117
Flip Lens	080926-69118-6	69118
Flip Lens	080926-69124-7	69124
TLR Remote Door/Switch Assy (TLR-1 Series/TLR-2 Series)	080926-69130-2	69130
TLR Remote Door/Switch Assy with "Safe Off" (TLR-1 Series/TLR-2 Series)	080926-69161-2	69161
TLR Remote Tape Switch Plug (TLR-1 Series/TLR-2 Series)	080926-69132-2	69132
Straight Remote tape switch fits most right-angle grips & other aftermarket accessories	080926-69134-6	69134
TLR Remote Pressure Switch Plug Coil (TLR-1 Series/TLR-2 Series) Shotgun coil remote switch allows for expansion of cord with pump action	080926-69135-3	69135
TLR Remote Pressure Switch Plug, Straight (TLR-1 Series/TLR-2 Series) Long gun remote switch attaches to rail forend with included clips	080926-69175-9	69175
TLR-1 Series/TLR-2 Series TLR Key Kit - Includes Rail Locating Keys for Glock style, 1913 Picatinny, S&W 99/TSW, and Beretta 90two and mounting tools	080926-69202-2	69202
Holster (Nylon)	080926-69901-4	69901
12 ga. Mag Tube Mount	080926-69902-1	69902
M-16/AR-15 Rail	080926-69906-9	69906
REM 870 Rail	080926-85175-7	85175
Lithium batteries (2) Pack	080926-85180-1	85180
Lithium batteries (6) Pack	080926-85177-1	85177
Lithium batteries (12) Pack	080926-85179-5	85179
Lithium batteries (400) Pack		



STREAMLIGHT



30 Eagleville Road • Eagleville, PA 19403 • 610-631-0600/800-523-7488 Phone • 610-631-0712/800-220-7007 Fax
 www.streamlight.com ©Streamlight, Inc. TLR-2 HLG 1/16

TLR Compatibility List

KEYS



The GL (Standard) system key appears somewhat thinner than the Picatinny key.

GL (Standard) keys fit Glock or “universal” rails. These have a cross slot about 5/32” wide.




The Picatinny key is wider than the GL (Standard) system key.

1913 (MIL-STD-1913 “Picatinny”) AND 1913 The 1913 key is wider than the standard key because the slots are nominally .206” wide. (A little more than 3/16”) The standard key will work with a Picatinny rail but the light will move back and forth with recoil unless the clamp is very tight. Some guns with a Picatinny rail still need a standard key depending on the construction of the actual rail. These will be identified for the individual guns when we test them.



The S&W key is a different shape than the other keys.

SMITH & WESSON AND TSW/99 keys have the bar extended farther back than the other keys. They are for rails having a non-standard (too short) distance between the slot and the trigger guard.



BERETTA 90two Looks like it has a Picatinny rail but dimensions are different.

Use the **90two** key for the TLR.

Note: M-lights should not be used on the 90two and will fall off under recoil.

Gun Compatibility List

BERETTA:

Cx4 Storm (carbine/rifle) – TLR fits with 1913 key.

Px4 Storm (Pistol) - TLR fits with standard key.
NOTE: M lights are VERY loose.

Vertec - New polymer key – 1913
Older aluminum key – GL (Standard).

CZ:

P-01 - Should work with GL (Standard) key. (Not tested; based on similar European version)

FN:

5.7 (with Picatinny style rail) -1913 key.

GLOCK:

Any with rails – GL (Standard) key

Cannot fit Glocks that ARE NOT equipped with factory rails.

After installing a contour remote on a TLR-2 equipped Glock it will likely be necessary to rezero the laser.

HK:

USP (full size) uses our HK adapter 69085 with a GL (Standard) key.
(compact) uses our HK adapter 69091 with a GL (Standard) key.

HK P2000 is supposed to have Picatinny rail. (NOT CHECKED)

HK P30 -1913 key.

NOTE: The rail tilts down slightly from the bore. This may result in laser zeroing difficulty closer than 50 feet (depending on the tolerances of the pistol and laser).

KIMBER:

TLE RLII (1911 with rail) – Picatinny key.

RUGER:

KP345 – GL (Standard) key.
SR-9 – GL (Standard) key

SIG SAUER:

GSR or 1911 Style with flat bottom rail - Picatinny key.

ANY ALUMINUM FRAME SIG WITH A ROUND BOTTOM RAIL:

Including the P220R, P229R, etc. The Sig round bottom rail departs from the true shape of both the 1913 and Universal standards and may cause an improper fit. The TLR will work with the 1913 key but THERE WILL BE DAMAGE to the finish of both the gun and the light. The retaining screw must be TIGHT.

Newer Sig P series guns are supposed to have a true Picatinny rail. This has not been verified by Streamlight.

SP2022 - Polymer frame. Same comments as for aluminum frames, EXCEPT that the polymer frame is a little thicker and does not show marks from a clamp because it is molded from black material. PER SIG, the TLR with the 1913 key works.

SMITH & WESSON:

On the **TSW** and **99** models, the slot is too far back for the standard key and requires the special S&W key. There are many different models of TSW, but as long as it's a **TSW WITH A RAIL**, it uses the S&W key.

Smith & Wesson **M&P** autoloader takes the Picatinny key.

SIGMA – Cannot fit.

SPRINGFIELD ARMORY:

Operator (1911 with rail) – Picatinny key.

XD (4 & 5 inch barrels) – GL (Standard) key. Cannot fit 3" barrel.

WALTHER:

99 - New (2004 models) FULL SIZE ones are nearly the same as the S&W 99 and use the S&W key.
Older ones (no slot across the rail and the side grooves CLOSED in front) cannot be fitted with a TLR.

99 Compact – Cannot fit. Rail is too short.

P22 – Cannot fit. Non-standard rail.

