



TLR-3[®]X

CUSTOMIZABLE, POLYMER, RAIL-MOUNTED LIGHT FOR USE WITH SUBCOMPACT AND COMPACT HANDGUNS



Multiple switch options



Available Colors: 

Designed for subcompact and compact handguns, the TLR-3X offers 500 lumens of brightness and a 161-meter beam distance for clear visibility. Made from durable polymer and tested for extreme temperatures, it provides reliable performance in challenging conditions.

Its slim profile, reversible rail clamps, and multiple paddle switches allow for a customizable fit across a wide range of firearms. The innovative mounting system enables quick, secure installation and removal—without placing your hands in front of the muzzle.

OUTPUT

LUMENS	500
CANDELA	6,500
DISTANCE	161m
RUN TIME SL-B9	1 hr
RUN TIME CR123A	1.5 hrs

ITEM NUMBERS

Description	UPC	Item #
TLR-3X (1913 Slim) - Includes mounting kit with key, paddles, multi-tool and (1) CR123A lithium battery - Black	080926-59102-8	59102
TLR-3X (SIG SAUER® P365®/XL closed rail systems) - Includes mounting kit with key, paddles, multi-tool and (1) CR123A lithium battery - Black	080926-59104-2	59104
TLR-3X (1913) - Includes mounting kit with keys, paddles, multi-tool and (1) CR123A lithium battery - Black	080926-59100-4	59100
TLR-3X USB (1913 Slim) - Includes mounting kit with key, paddles, multi-tool and (1) SL-B9 battery - Black	080926-59103-5	59103
TLR-3X USB (SIG SAUER® P365®/XL closed rail systems) - Includes mounting kit with key, paddles, multi-tool and (1) SL-B9 battery - Black	080926-59105-9	59105
TLR-3 X USB (1913) - Includes mounting kit with keys, paddles, multi-tool and (1) SL-B9 battery - Black	080926-59101-1	59101

KEY FEATURES

- Impact and chemical-resistant, heat-stabilized polymer construction
- Reversible jaws for compatibility across compact/sub compact pistols
- One-handed snap on tighten interface keeps hands away from muzzle when attaching and detaching

BATTERY

- Multi-Fuel: Accepts one SL-B9® rechargeable battery or one CR123A lithium battery
- SL-B9 battery charges within 2.5 hours with optional USB-C cord or bank charger; rechargeable up to 500 cycles

MATERIAL/DURABILITY

- Impact-resistant polymer construction with durable anodized aluminum facecap
- High temperature, shock-mounted, impact-resistant BOROFLOAT® glass lens
- IPX7 waterproof to 1m for 30 minutes

DIMENSIONS

LENGTH: 2.75 in (6.99 cm)

WEIGHT: SL-B9 2.25 oz (63.8g) // CR123A 2.15 oz (60.9g)

WARRANTY

Limited lifetime warranty
Visit streamlight.com for full warranty information

ACCESSORIES

	Description	UPC	Item #
	CR123A Lithium Batteries- 2 Pack	080926-85175-7	85175
	CR123A Lithium Batteries - 6 Pack	080926-85180-1	85180
	CR123A Lithium Batteries - 12 Pack	080926-85177-1	85177
	CR123A Lithium Batteries - 400 Pack	080926-85179-5	85179
	SL-B9 Rechargeable Battery - 2 Pack	080926-20237-5	20237
	SL-B9 Rechargeable Battery - 8 Pack	080926-20238-2	20238
	22" (55.88 cm) USB-C Cord	080926-22084-3	22084
	Y-Split USB-C Cord	080926-22090-4	22090
	8-Unit SL-B9 Bank Charger - 120V/100V AC	080926-20231-3	20231
	8-Unit SL-B9 Bank Charger - 230V/240V AC	080926-20232-0	20232
	8-Unit SL-B9 Bank Charger - 12V DC <i>Batteries not included</i>	080926-20230-6	20230
	8-Unit SL-B9 Bank Charger - 120V/100V AC	080926-20234-4	20234
	8-Unit SL-B9 Bank Charger - 230V/240V AC	080926-20235-1	20235
	8-Unit SL-B9 Bank Charger - 12V DC <i>Batteries included</i>	080926-20233-7	20233
<i>No Image Available</i>	TLR-3X 1913 Clamp Paddle Kit	080926-59106-6	59106
	TLR-3X 1913 Slim Clamp Paddle Kit	080926-59107-3	59107
	TLR-3X P365 Clamp Paddle Kit	080926-59108-0	59108