



STREAMLIGHT®

TLR-7® X SUB USB // TLR-7® X SUB

MULTI-FUEL, RAIL-MOUNTED LIGHT FOR SUBCOMPACT HANDGUNS



High Switch



Low Switch



Available Colors:



The TLR-7 X sub features a specialized clamp system and includes high and low paddle switches to match your shooting style. Multi-fuel design – runs on one rechargeable SL-B9® battery pack or one CR123A lithium battery.

OUTPUT

	SL-B9	CR123A
LUMENS	725	550
CANDELA	7,700	5,000
DISTANCE	176m	141m
RUN TIME	1 hr	1.5 hrs

ITEM NUMBERS

Description	UPC	Item #
TLR-7 X sub (GLOCK® 43X/48 MOS 43X/48 Rail) - Includes mounting kit with key, multi-tool and (1) CR123A lithium battery	080926-69400-2	69400
TLR-7 X sub (SIG SAUER® P365®/XL closed rail systems) - Includes mounting kit with key, multi-tool and (1) CR123A lithium battery	080926-69401-9	69401
TLR-7 X sub (1913) - Includes mounting kit with key, multi-tool, and (1) CR123A lithium battery	080926-69402-6	69402
TLR-7 X sub (1913OS) - Includes mounting kit with key, multi-tool and (1) CR123A lithium battery	080926-69404-0	69404
TLR-7 X sub USB (GLOCK® 43X/48 MOS 43X/48 Rail) - Includes mounting kit with key, multi-tool, (1) SL-B9 battery pack and USB-C cord	080926-69405-7	69405
TLR-7 X sub USB (SIG SAUER® P365®/XL closed rail systems) - Includes mounting kit with key, multi-tool, (1) SL-B9 battery pack and USB-C cord	080926-69406-4	69406
TLR-7 X sub USB (1913) - Includes mounting kit with key, multi-tool, (1) SL-B9 battery pack and USB-C cord	080926-69407-1	69407
TLR-7 X sub USB (1913OS) - Includes mounting kit with key, multi-tool, (1) SL-B9 battery pack and USB-C cord	080926-69408-8	69408

KEY FEATURES

- Front-loading battery capability
- “Safe-off” feature prevents accidental activation, saves batteries
- User interchangeable paddle switches

BATTERY

- Multi-fuel: Accepts one SL-B9 rechargeable battery pack or one CR123A lithium battery
- SL-B9 battery pack charges within 2.5 hours via USB-C cord or bank charger; rechargeable up to 500 cycles

MATERIAL/DURABILITY

- 6000 Series machined aircraft aluminum with black anodized finish
- Switch housing: Impact- and chemical-resistant engineered polymer
- High temperature, shock-mounted, impact-resistant BOROFLOAT® glass lens
- IPX7 waterproof to 1m for 30 minutes

DIMENSIONS

LENGTH: 2.51 in (6.38 cm)

WEIGHT: SL-B9 2.64 oz (74.8g) // CR123A 2.39 oz (67.8g)
W/ BATTERY

WARRANTY

Limited lifetime warranty
Visit streamlight.com for full warranty information

	Description	UPC	Item #
	CR123A Lithium Batteries - 2 Pack CR123A Lithium Batteries - 6 Pack CR123A Lithium Batteries - 12 Pack CR123A Lithium Batteries - 400 Pack	080926-85175-7 080926-85180-1 080926-85177-1 080926-85179-5	85175 85180 85177 85179
	SL-B9 USB-C Rechargeable Battery Pack - 2 Pack SL-B9 USB-C Rechargeable Battery Pack - 8 Pack	080926-20237-5 080926-20238-2	20237 20238
	22" (55.88 cm) USB-C Cord	080926-22084-3	22084
	Tail Cap Assembly	080926-69492-7	69492
	Clamp Jaw Kit - GLOCK® 43X/48 MOS 43X/48 Rail	080926-69320-3	69320
	Clamp Jaw Kit - 19130S	080926-69321-0	69321
	Clamp Jaw Kit - 1913	080926-69322-7	69322
	Clamp Jaw Kit - SIG SAUER® P365®/XL (closed rail systems)	080926-69323-4	69323