

VANTAGE®

HELMET-MOUNTED LIGHT



Fits snugly against the helmet both below and above the brim



Blue taillight ensures visibility from behind



Features reflective strip on LED housing



Available Colors: 

Compact and low-profile, the Vantage® helmet light is built for firefighting and industrial use, mounting securely above or below full-brim helmets. Its clamp allows fast, tool-free battery changes when installed under the brim, and an ambidextrous tail switch ensures reliable activation even with bulky gloves. A high-candela LED delivers a focused beam that cuts through smoke and haze without washing out peripheral vision, improving awareness in low-visibility conditions. An ultra-bright blue taillight enhances personnel visibility, while the sealed, water-resistant build ensures dependable performance in harsh environments.





OUTPUT

LUMENS	225
CANDELA	22,000
DISTANCE	297m
RUN TIME	5 hrs

ITEM NUMBERS

Description	UPC	Item #
Vantage - Includes (2) CR123A lithium batteries - Black	080926-69140-7	69140

ACCESSORIES

	Description	UPC	Item #
	CR123A Lithium Batteries - 2 Pack	080926-85175-7	85175
	CR123A Lithium Batteries - 6 Pack	080926-85180-1	85180
	CR123A Lithium Batteries - 12 Pack	080926-85177-1	85177
	CR123A Lithium Batteries - 400 Pack	080926-85179-5	85179

KEY FEATURES

- Lightweight, compact design easily attaches/detaches above or below brim on fire helmets, industrial helmets, and hard hats
- Fits both traditional and modern style helmets
- Replace batteries without removing the light from the helmet when mounted below the brim

BATTERY

- Powered by two 3-volt CR123A lithium batteries

MATERIAL/DURABILITY

- 6000 Series machined aircraft aluminum with black anodized finish
- High-impact, chemical-resistant polymer LED housing
- High temperature, impact-resistant BOROFLOAT® glass lens
- IPX7 waterproof to 1m for 30 minutes

DIMENSIONS

LENGTH: 3.08 in (7.82 cm)
WEIGHT: 5.08 oz (144g)
 W/ BATTERIES

RATINGS

- Flashlight meets 500°F requirements of NFPA 1970-14.2 (2025)

WARRANTY

Limited lifetime warranty
 Visit streamlight.com for full warranty information