



VULCAN® LED ATEX

ATEX-RATED RECHARGEABLE LANTERN



Toggle switch is easy to use with gloved hands



Available Colors: ●

Lightweight ATEX-rated rechargeable lantern. It produces a tight beam that is optimal for firefighting operations. The lantern includes a momentary switch providing programmable access to various modes of operation.

KEY FEATURES

- Features the latest in LED technology for extreme brightness
- Two available models: Standard System with AC/DC and Vehicle Mount with 12V DC direct wire charging rack; both models include a quick release buckle strap
- Fits existing Vulcan® series charging bases/racks

OUTPUT

	HIGH	LOW
LUMENS	180	70
CANDELA	100,000	40,000
DISTANCE	632m	400m
RUN TIME	3.5 hrs	7.5 hrs

Blink mode runs 5.5 hrs

ITEM NUMBERS

Description	UPC	Item #
Vulcan LED ATEX - 230V AC /12V DC - Includes quick release shoulder strap	080926-44753-0	44753
Vulcan LED ATEX - 240V AC/12V DC - Includes quick release shoulder strap	080926-44752-3	44752
Vulcan LED ATEX - 100V AC/12V DC - Includes quick release shoulder strap	080926-44754-7	44754
Vulcan LED ATEX - Vehicle Mount System - 12V DC - Includes quick release shoulder strap	080926-44751-6	44751
Vulcan LED ATEX (Without Charger) - Includes quick release shoulder strap	080926-44750-9	44750

BATTERY

- Two lightweight lithium-ion nanotechnology cells
- Recharges in 5 hours

MATERIAL/DURABILITY

- Housing and face cap made from high-impact, anti-static, non-conductive, super-tough nylon lens. One-way valve for case venting
- Rubberized cushioned-grip handle
- IP66 dust-tight and water-resistant
- 2m impact resistance tested

DIMENSIONS

LENGTH: 19.76 cm

WEIGHT: 875.4g

SAFETY RATINGS

- ATEX: II 3G Ex ec ic IIC T5 Gc;
II 3D Ex tc IIIC T54°C Dc; FTZU 08 ATEX 0139X
- IECEX: Ex ec ic IIC T5 Gc; Ex tc IIIC T54°C Dc; IECEX FTZU 15.0038X
- Charging rack meets requirements of NFPA 1900-11.1.11.2 (2024) mounted in any position

WARRANTY

Limited lifetime warranty
Visit streamlight.com for full warranty information

ACCESSORIES

	Description	UPC	Item #
	120V AC Charge Cord	080926-22060-7	22060
	230V AC Charge Cord	080926-22061-4	22061
	240V UK AC Charge Cord	080926-22062-1	22062
	12V DC2 Charge Cord	080926-22050-8	22050
	12V DC1 Charge Cord	080926-22051-5	22051
	Li-Ion Battery	080926-44610-6	44610
	Standard System Charge Rack*	080926-44102-6	44102
	Direct Wire DC Charge Rack*	080926-44132-3	44132
	AC/DC Smart Charge Rack*	080926-44103-3	44103
	Quick Release Strap	080926-44050-0	44050
	Heavy-Duty Shoulder Strap	080926-45232-9	45232
No Image Available	24 Volt Direct Wire to 12 Volt Charge Converter	080926-22093-3	22093

**cords not included*