



WAYPOINT®

LONG-RANGE, PISTOL-GRIP SPOTLIGHT



Integrated stand for hands-free lighting



Includes high-strength lanyard



Polymer storage mount accessory



Available Colors:



The lightweight, alkaline battery-powered Waypoint shines bright, producing 750 lumens with a far-reaching 775-meter beam. This long-range spotlight is perfect for long distance illumination.

KEY FEATURES

- Trigger-style switch; secondary rotary switch for mode selection
- High/Low/Emergency Signal modes
- Cushioned handle and integrated stand for scene lighting

OUTPUT

	HIGH	LOW
LUMENS	750	60
CANDELA	150,000	12,000
DISTANCE	775m	219m
RUN TIME	10 hrs	92 hrs

Emergency Signal: Runs 82 hours

Unlimited run time with 12V DC power cord

ITEM NUMBERS

Description	UPC	Item #
Waypoint - Includes 12V DC power cord and polymer mount/holder - Box - Yellow	080926-44900-8	44900
Waypoint - Includes 12V DC power cord and polymer mount/holder - Box - Black	080926-44902-2	44902
Waypoint - Includes 12V DC power cord - Blister - Black	080926-44905-3	44905

BATTERY

- Operates using batteries or via 12V DC power cord
- Powered by four C alkaline batteries (not included)
- 12V DC power cord (included) provides unlimited run time (not a charge cord, does not charge batteries. Waypoint uses alkaline batteries)

MATERIAL/DURABILITY

- High-impact polycarbonate housing
- O-ring sealed polycarbonate lens
- Rubberized lens ring and cushioned-grip handle
- IPX4 water-resistant; 1m impact resistance tested
- Optional filters constructed of flexible thermoplastic elastomer with polycarbonate lens; help preserve night vision

DIMENSIONS

LENGTH: 6.75 in (17.15 cm)

WEIGHT: 1.8 lbs (816g)
W/ BATTERIES

WARRANTY

Limited lifetime warranty

Visit streamlight.com for full warranty information

ACCESSORIES

	Description	UPC	Item #
	Waypoint 12V DC power cord (62.5"; 1.5m) <i>(This is a power cord only. Does not charge batteries)</i>	080926-44903-9	44903
	Waypoint Mount/Holder	080926-44908-4	44908
	Waypoint Filter - Red	080926-44924-4	44924
	Waypoint Filter - Green	080926-44925-1	44925